

NM Oil Cons. Commission

Drawer DD

Artesia, NM 88210

OPERATOR'S COPY

Form 9-331  
Dec. 1973UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐2. NAME OF OPERATOR  
Premier Production Company ✓3. ADDRESS OF OPERATOR  
324 W. Main, Artesia, NM 882104. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 990' FSL, 1650' FWL  
AT TOP PROD. INTERVAL: 2812'  
AT TOTAL DEPTH: 2812'

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Cement

## SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐5. LEASE  
NM 17223

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Alice Federal9. WELL NO.  
210. FIELD OR WILDCAT NAME  
Turkey Track, SR, Q, GB, SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 23, T-18S, R-29E

12. COUNTY OR PARISH  
Eddy13. STATE  
NM

14. API NO.

30-015-24970

15. ELEVATIONS (SHOW DF, KDB, AND WD)

~~2800'~~ 3483' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9/28/84 spud well 12:45PM; drill 12½" hole w/fresh water, spud mud to 370'. Run 354' (9 joints) 8-5/8" new 24# casing w/Texas-pattern shoe & 1 centralizer on bottom collar. Cemented w/100sax Halliburton lite 10# gilsonite, 200 sax Class C 2% CalCl. Cement came within 60' of surface; reddy mix to surface w/8yds. WOC 18hrs; plug down 9:10PM.

9/19 Drill plug out w/7-7/8" bit & press. test to 600# for 30min. Cont. drilling 7-7/8" hole w/brine water to 2812'. 9/23 run 69 joints 5½" (2804') 17# new API casing w/guide shoe & latch down plug, insert float & 10 centralizers. Cement w/1000gal flo check 21, 900 sax Halliburton lite w/15# salt, ¼# flo cele & 600 sax Class C w/6# salt, 3/10 of 1% CFR-2. Circulated 250sax to pit; plug down 8:20PM. 9/23 8:30PM Released rig.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED \_\_\_\_\_

TITLE Operator

DATE 9/26/84

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

CONDITIONS OF APPROVAL OCT 2 1984

Caldwell

NEW MEXICO

\*See Instructions on Reverse Side

RECEIVED BY \_\_\_\_\_

OCT 03 1984

Form Approved

Budget Bureau No. 42-R1424

ARTEZIA, NM