

UNITED STATES

Form Approved  
Budget Bureau No. 42-R1424

RECEIVED BY

DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

JAN 31 1985

SUNDRY NOTICES AND REPORTS ON WELLS  
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331 for such proposals.)

ARTESIA, OFFICE

well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR ARCO Oil and Gas Company  
Division of Atlantic Richfield Company

3. ADDRESS OF OPERATOR

P. O. Box 1710, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FNL & 860' FEL

AT TOP PROD. INTERVAL: as above

AT TOTAL DEPTH: as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

Log, Run Prod Csg & Cmt  
Perf, Treat & Complete

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Finished drlg 7-7/8" hole to 2150' TD @ 4:45 AM 10/9/84. Ran GR-DIL & GR-CNL/LDT w/caliper. RIH w/5 1/2" OD 14# K-55 csg, set @ 2150'. FC set @ 2100'. Cmt'd 5 1/2" OD csg w/150 sx BJ-Lite followed by 200 sx Cl H Neat cmt. Circ 40 sx cmt to surf. PD @ 3:00 AM 10/10/84. On 10/14/84 tagged PBD @ 2099'. Perf'd w/1 JSPF @ 2018, 19, 24, 2027'. RIH w/RBP & pkr. Set BP @ 2078' & pkr @ 1899'. Acidized perfs 2018-2027' w/2000 gals 15% HCL-NEFE w/2% KCL wtr. On 3 1/2 hr swab test, rec 4 BW. Rel pkr. Retr BP. RIH w/cmt retr. Set retr @ 1998'. Cmt sqzd perfs 2018-27' w/75 sx Cl H Neat cmt. PO of retr & spot 10 sx on top. Tagged TOC @ 1980' new PBD. Perf'd w/1 JSPF @ 1886, 96, 1902, 09, 43, 48, 59, 60, 66, 72, 1974' = 11 .41" holes. RIH w/pkr & set @ 1774'. Acidized perfs 1886-1974' w/5200 gals 15% HCL-NEFE. On 10/19/84 swbd 10 hrs, rec 7 BO, 25 BW. Frac'd perfs 1886-1974' w/29,000 gals Mini-Max III, 45,000# 20/40 sd, 22,500# 20/20 sd. Flushed w/2% KCL wtr. Swbd 1 hr, rec 3 BO, 236 BW. On 10/25/84 flwd & swbd 13 BO & 40 BW in 3 hrs. (cont'd on page #2)

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Elizabeth S. Bush

TITLE Drlg. Engr.

DATE 1/24/85

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

APPROVED FOR RECORD

TITLE

DATE

JAN 29 1985

\*See Instructions on Reverse Side

NEW MEXICO