	<u> </u>
Form 9-331 Dec. 19781 0.25 CONT. CC SSION	Form Approved. Budget Bureau No. 42-R1424
Drawer DD UNITED STATES	5. LEASE NM - 23414
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen of the back to a Configrent reservoir. Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME
1 - 1	B. FARM OR LEASE NAME Travis "E" Federal
1. OII Well XX     gas well other     O. C. D.       2. NAME OF OPERATOR     ARTESIA, OFFICE	9. WELL NO.
Anadarko Production Company / 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Loco Hills-Queen-Grayburg-SA
P. O. Drawer 130, Artesia, New Mexico 88210 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
below.) AT SURFACE: 1980' FSL & 600' FWL	6 - 185 - 29E 12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH: Same	Eddy New Mexico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3663.7 GL
TEST WATER SHUT OFF	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
(other) X Spud, drill TL	), set & cement surface & production
<ol> <li>DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner</li> <li>Rigged up rotary tools; spudded 12½" hole @ 1: with fresh water native mud.</li> <li>Ran 8-5/8", 24.0#, K-55 casing with casing sho with 300 sx Class H w/2% CaCl. PD @ 2:00 PM 1</li> <li>Installed BOP &amp; pressure tested to 1000#. WOO plug on 8-5/8" with 7-7/8" bit. Drilled to TE Ran Open Hole Logs.</li> <li>Ran 5½", 15.5# casing with casing shoe @ 2829" 700 sx Pacesetter Lite and tailed-in with 300 AFS + 5# Salt/sx. PD @ 2.45 PM 10-28-84; circ</li> </ol>	<pre>lirectionally drilled, give subsurface locations and nt to this work.)* 00 AM 10-22-84; drilled to 355' KB be @ 352' KB. Western Co. cemented 0-22-84; circulated 70 sx to pit. C total of 18 hours prior to drillin 0 - 2836' with 10# brine water. ' KB. Western Co. cemented with 0 sx Class C with .6% CF-1 &amp; .2% culated 200 sx to pit.</pre>
<u>Note</u> : Will file appropriate forms upon comple	etion of well.
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED THE Field Foreman	DATE October 30, 1984
APPROVED BY (This space for Federal or State off CONDITIONS OF APPROVAL, IFANY: 1984	ice use) DATE
Carlebaty NEW MEXICO *See Instructions on Reverse S	

,