NEW MEXICO OIL CONSERVATION COMMISSION DRAWER DD ARTESIA, NEW MEXICO

•

| FIELD REPORT FOR CEMENTING OF WELLS | | | | | | | Elps. 4-19-85 | |
|--|-----------|----------------------------|---------------|-----------------------------|-----------------------|-----------------|----------------|--|
| Operator Blanco Eng. Inc. | | | Lease Scripps | | | Well | [#] 5 | |
| Location of Well | Unit L | Section 25 | | Townsh /8 | rip Rang 26 | ge Count Edd | • | |
| Drilling Contractor | | | | Type of Equipment Rotaey | | | | |
| * = CSG. TO WITNESS APPROVED CASING PROGRAM | | | | | | | | |
| Size of Hole | Size | of Casing | Weigh Foo | t Per t | New or Us | sed Depth | Sacks Cemen | |
| * 121/4 | 8 5/8" | | z4 # | | NEW | 930 | circ | |
| 77/8 | | 85kg" 51/2 ["] | 15, | 5# | 1 1 | 3750 | are | |
| | | | | | | | | |
| Casing Data: | | | | | | | | |
| Surface joints of $8\frac{1}{24}$ inch 24 # Grade $\overline{J-55}$ | | | | | | | | |
| (Approved) (Rejected) Inspected by <u>BWWeaver</u> datedate | | | | | | | | |
| Cementing Program | | | | | | | | |
| Size of hole <u>12 hr</u> Size of Casing <u>857</u> Sacks coment required <u>200</u> | | | | | | | | |
| Type of Shoe used Tex-Par Float collar used Tarsert Btm 3 jts welded Yes | | | | | | | | |
| TD of hole 955 Set 954 Feet of 89 Inch 24 # Grade J-55 | | | | | | | | |
| New-used csg. @ 954 with 500 sacks neat cement around shoe | | | | | | | | |
| +additives_22.cc | | | | | | | | |
| Plug down @(AM) (PM) Date | | | | | | | | |
| Cement circulated yesNo. of Sacks 30Cemented by DewtonWitnessed by BWWeaver | | | | | | | | |
| Temp. Survey ran @(AM) (PM) Datetop cement @ | | | | | | | | |
| Casing test @(AM) (PM) DateCop cement e | | | | | | | | |
| Method Used Witnessed by | | | | | | | | |
| Checked for shut off @ (AM) (PM) Date | | | | | | | | |
| Method used Witnessed by | | | | | | | | |
| Remarks: Last Drilling Break 824 | | | | | | | | |