

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

NM 001-122, 001-12300  
SUBMIT IN TR. LICATE\*  
(Other instructions on re-  
lease side) 88210

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Yates Drilling Company

3. ADDRESS OF OPERATOR

105 South 4th Street, Artesia, New Mexico 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

1980' FSL & 2310' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3535' GR

MAR 14 '88

O. C. D.

ARTESIA, OFFICE

5. LEASE DESIGNATION AND SERIAL NO.

LC-067132

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Denton Federal

9. WELL NO.

9

10. FIELD AND POOL, OR WILDCAT

Loco Hills, Qn-GRB-SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 20-18S-29E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Well has been temporarily abandoned and has not produced.

Recently well began to flow water from casing. We propose to plug back, as follows:

1. Set cast iron bridge plug at 2628' above perforations 2678'-2800'.
2. Dump 35' of cement on CIBP.
3. Set CIBP at 2401' above perforations 2451'-2506'.
- \* 4. Leave casing valve open to existing production facilities and monitor water flow.
5. We then wish to temporarily abandon well until decision to P&A or produce is made.

→ csq. integrity test (SJS)

RECEIVED  
FEB 26 12 41 PM '88  
CARLOS J. RODRIGUEZ  
AREA HEADQUARTERS

18. I hereby certify that the foregoing is true and correct

SIGNED

John Rhoden

TITLE

Engineer

DATE

2-25-88

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

3-11-88

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side