

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

437

5. LEASE DESIGNATION AND SERIAL NO.

LC - 058581

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. STATE AGREEMENT NAME

Ballard Grayburg
San Andres Unit

8. FARM OR LEASE NAME

Tract No. 10

9. WELL NO.

9

10. FIELD AND POOL, OR WILDCAT

Loco Hills-Queen-G-SA

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

4 - 18S - 29E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether OF, RT, GR, etc.)

3536.1' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Spud; drill TD; set & cmt csg
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. Rigged up Rotary Tools.
2. Spudded 12 1/2" hole @ 0115 hrs 5-21-85. Drilled to 323' with Fresh Water native mud. Lost circulation @ 70'; dry drilled to 323' KB.
3. Ran 8-5/8", 24.0#, K-55, ST&C casing; set casing shoe @ 298' KB and Baffle Plate @ 266' KB. Dowell cemented with 200 sx Lite w/2% CaCL, 10# Kolite (Gilonite)/sx & 1/4# Celloflake/sx and tailed-in with 200 sx Class H w/2% CaCL. PD @ 0100 hrs 5-22-85; did not circulate cement. Redmixed to surface with 8 yards..
4. Installed BOP and pressure-tested - O. K. WOC a total of 18 hours prior to drilling plug on 8-5/8" with 7-7/8" bit using 10# brine.
5. Drilled to TD of 2900'.
6. Schlumberger ran Open Hole Logs.
7. Ran 4 1/2", 10.5#, K-55, ST&C casing; set casing shoe @ 2892' KB. Dowell cemented with 1000 sx Lite with 5# Salt/sx & 1/4# Celloflake/sx and tailed-in with 200 sx Class C with .2% Friction reducer & .6% fluid-loss additive. PD @ 1645 hrs 5-28-85; circulated 200 sx to pit. Presently waiting on completion.

Note: Will file appropriate forms upon completion of well.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Supervisor

DATE

June 6, 1985

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

JUL 1 1985

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

PRIVACY ACT

The Privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et. seq., 351 et. seq., 25 U.S.C. et. seq.; 43 CFR 3160.
PRINCIPAL PURPOSE: The information is to be used to evaluate, when appropriate, approve applications, and report completion of secondary well operations, on a Federal or Indian lease.

ROUTINE USES: (1) Evaluate the equipment and procedures used during the proposed or completed subsequent well operations. (2) Request and grant approval to perform those actions covered by 43 CFR 3162.3-2(2). (3) Analyze future applications to drill or modify operations in light of data obtained and methods used. (4)(5) Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions.

EFFECT OF NOT PROVIDING INFORMATION: Filing of this notice and report and disclosure of the information is mandatory once an oil or gas well is drilled.

The Paperwork Reduction Act of 1980 (44 U.S.C. 3501, et. seq.) requires us to inform you that:

This information is being collected in order to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

This information will be used to report subsequent operations once work is completed and when requested, to obtain approval for subsequent operations not previously authorized.

Response to this request is mandatory for the specific types of activities specified in 43 CFR Part 3160.