

RECEIVED BY DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-42410

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Comstock Federal

9. WELL NO.

#1

10. FIELD AND POOL, OR WILDCAT  
Artesia Oil Pool11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 12-18S-27E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3593' GR

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other) bottom casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Well was drilled to a Total Depth of 2400' at 1:00 am on 12/17/84

Ran Density-Neutron log &amp; Dual Laterolog

Ran 2400' fo 5½", 17#-14# J055 casing

Cemented with 250 sks Lite, 8# salt, ¼# of flocele and

350 sks Class "C", 6# salt, .3% CFR-2

Pump plug on 12-18-84, 2:30 am

Pressure tested 1000# for 30 minutes-Held fine

BLM notified via Halliburton dispatcher

Circulated 45 sks to pit

WOC 72 hours.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Production Clerk

DATE

1/2/85

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL JAN 4 1985

Carlsbad,

NEW MEXICO See Instructions on Reverse Side

