

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Exp. 5-20-84

Operator <u>Yates</u>		Lease <u>NIX GP</u>		Well # <u>2</u>	
Location of Well	Unit <u>0</u>	Section <u>22</u>	Township <u>18 S</u>	Range <u>26 E</u>	County <u>EDDY</u>
Drilling Contractor	<u>AFT #2</u>		Type of Equipment <u>ROTARY</u>		

* = CSG. TO WITNESS

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cemen
* 12 1/4"	8 5/8	24 #	NEW	900	Circ
7 7/8"	5 1/2	14 #	"	1800	Circ

Casing Data:

Surface 27 joints of 8 5/8 inch 24 # Grade J-55

yes (Approved) (Rejected)

Inspected by B.W. Weaver date 12-5-84

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 150

Type of Shoe used Tex-Pat Float collar used Insert Btm 3 jts welded yes

TD of hole 912 Set 909 Feet of 8 5/8 Inch 24 # Grade J-55

New-~~used~~ csg. @ 909 with 150 sacks neat cement around shoe

+ 200 sax Pace Setter additives 2% CC

Plug down @ 5:00 (AM) (PM) Date 12-5-84

Cement circulated yes No. of Sacks 15

Cemented by Western Witnessed by B.W. Weaver

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: