

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Exp. 5-20-84

Operator <u>YPC</u>		Lease <u>Flint GU</u>		Well # <u>3</u>	
Location of Well	Unit <u>I</u>	Section <u>22</u>	Township <u>18</u>	Range <u>26</u>	County <u>EDDY</u>
Drilling Contractor	<u>AFT #2</u>		Type of Equipment <u>ROTARY</u>		

* = CSG. TO WITNESS

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cemen
* 12'4	8 5/8"	24 ⁺	NEW	950	CIRC
7 7/8	5 1/2"	14 #	"	1800	CIRC

Casing Data:

Surface 24 joints of 8 5/8 inch 24 # Grade J-55

Yes (Approved) (Rejected)

Inspected by BW Weaver date 12-9-84

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 150

Type of Shoe used Tex-Par Float collar used Insert Btm 3 jts welded Yes

TD of hole 864 Set 865 Feet of 8 5/8 Inch 24 # Grade J-55

New-used csg. @ 865 with 150 sacks neat cement around shoe

+ 250 sax Pace Setter ltc additives 20% CC

Plug down @ 7:00 (AM) (PM) Date 12-10-84

Cement circulated Yes No. of Sacks 75

Cemented by Western Witnessed by

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Last Drilling Break 745