

Form 3160-5
(November 1983)

UNITED STATES

SUBMIT IN TRIPI
(Other instructions
verse side)

TE*

Form approved.

Budget Bureau No. 1004-0135
Expires August 31, 1985

43F

RECEIVED BY

Artesia, NM

DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT

JAN 2 - 1984

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use APPLICATION FOR PERMIT for such proposals.)

O. C. D.

ARTESIA OFFICE

OTHER

2. NAME OF OPERATOR

MYCO Industries, Inc. ✓

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

1980 FSL & 1980 FEL, Sec. 35-T18S-R29E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3412' GR

5. LEASE DESIGNATION AND SERIAL NO.

LC 062069

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Roadrunner Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

South Leo Queen Grayburg - SA

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Unit J, Sec. 35-T18S-R29E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-23-84. Spudded 12-1/4" hole 7:45 AM 12-23-84. Set 40' of conductor pipe.
Ran 8 joints 8-5/8" 24# K-55 ST&C casing set 336'. 1-Texas Pattern notched guide shoe set 336'. Insert float set 296'. Cemented w/100 sx Pacesetter Lite w/2% CaCl2, 1/4#/# sack celloseal and 7#/# sack Hiseal. Tailed in w/100 sx Class C w/2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 3:15 PM 12-23-84. Bumped plug to 1000 psi, released pressure and float held okay. Cement did not circulate. WOC 6 hours.
Ran 1". Tagged cement 231'. Spotted 30 sx C1 C w/4% CaCl2. PD 8:15 PM 12-23-84. WOC 2 hrs and 5 mins. Ran 1". Tagged cement 158'. Spotted 50 sx C1 C w/4% CaCl2. PD 10:40 PM 12-23-84. WOC 1 hr and 50 mins. Ran 1". Tagged cement 150'. Spotted 50 sx C1 C w/4% CaCl2. PD 1:00 AM 12-24-84. WOC 2 hrs. Ran 1". Tagged cement 150'. Spotted 50 sx C1 C w/4% CaCl2. PD 3:30 AM 12-24-84. WOC 2 hrs. Ran 1". Tagged cement 150'. Spotted 25 sx C1 C w/4% CaCl2. PD 6:00 AM 12-24-84. WOC 2 hrs. Ran 1". Tagged cement 126'. Spotted 25 sx C1 C w/4% CaCl2. PD 9:00 AM 12-24-84. WOC 3 hrs. Ran 1". Tagged cement 58'. Spotted 25 sx C1 C w/4% CaCl2. PD 12:30 PM 12-24-84. Cement circulated. WOC. Drilled out 12:15 PM 12-26-84. WOC 69 hours. Nippled up and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Production Supervisor

DATE 12-27-84

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL DEC 31 1984

Carlsbad

NEW MEXICO

*See Instructions on Reverse Side