

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWN BY
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Exp. 7-3-85

Operator	YPC		Lease	SYLVESTER ABC		Well #	1
Location of Well	Unit	Section	Township	Range	County		
	P	8	18S	25E	EDDY		
Drilling Contractor	BOBCAT DRLLNG.		Type of Equipment		ROTARY		

* = CSG. TO WITNESS

APPROVED CASING RECORD

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 3/4	13 3/8	48 #	NEW	350'	CIRC
* 12 1/4	8 5/8	24 #	"	1000'	CIRC
7 7/8	5 1/2	15.5 or 17 #	"	TD 7600'	CIRC

Casing Data:

Surface 29 joints of 8 5/8 inch 24 # Grade J-55
 Yes (Approved) (Rejected)
 Inspected by B.W. date 1-18-85

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 200
 Type of Shoe used Tex-Ar Float collar used Insert Btm 3 jts welded Yes
 TD of hole 1130 Set 1130' Feet of 8 5/8 inch 24 # Grade J-55
 New-used csg. @ 1138 with 200 sacks neat cement around shoe
 + 400 sack Pace Setter Lite additives 3% CC
 Plug down @ 3:15 (AM) (PM) Date 1-18-85
 Cement circulated No No. of Sacks -0-
 Cemented by Western Witnessed by B.W.
 Temp. Survey ran @ 9:30 (AM) (PM) Date 1/18/85 Top cement @ 510'
 Casing test @ (AM) (PM) Date
 Method Used Witnessed by
 Checked for shut off @ (AM) (PM) Date
 Method used Witnessed by

Remarks: Loss Circulation @ 430

Last dily break @ 1063'
 Last circ. @ 510'

1. Ran 1" + tagged to c @ 460'
 cnt w/ 100 sx C 2% cc
2. Ran 1" + tagged to c @ 410'
 cnt w/ 50 sx
3. Ran 1" + tagged to c @ 410'
 cnt w/ 75 sx
4. Ran 1" + tagged to c @ 410'
 cnt w/ 150 sx