

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
Lwr.							
T. Anhy	T. Canyon	7381	T. Ojo Alamo	T. Penn. "B"			
T. Salt	T. Strawn	7868	T. Kirtland-Fruitland	T. Penn. "C"			
D. Salt	T. Atoka	8182	T. Pictured Cliffs	T. Penn. "D"			
T. Yates	T. Miss		T. Cliff House	T. Leadville			
T. 7 Rivers	T. Devonian		T. Menefee	T. Madison			
T. Queen	T. Silurian		T. Point Lookout	T. Elbert			
T. Grayburg	T. Montoya		T. Mancos	T. McCracken			
T. San Andres	T. Simpson	560	T. Gallup	T. Ignacio Qtzite			
T. Glorieta	T. McKee	2116	Base Greenhorn	T. Granite			
T. Paddock	T. Ellenburger		T. Dakota	T.			
T. Blinberry	T. Gr. Wash		T. Morrison	T.			
T. Tubb	T. Granite		T. Todillo	T.			
T. Drinkard	T. Delaware Sand		T. Entrada	T.			
T. Abo	T. Bone Springs	4066	T. Wingate	T.			
T. Wolfcamp	T. Morrow Clastic	5170	T. Chinle	T.			
T. Penn.	T. Chester	8378	T. Permian	T.			
T. Cisco (Bough C)		8571	T. Penn. "A"	T.			
		6465					

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....	feet
No. 2, from.....to.....	feet
No. 3, from.....to.....	feet
No. 4, from.....to.....	feet

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	330	330	Surface, Redbeds				
330	1175	845	Redbeds, Anhydrite				
1175	2240	1065	Dolomite				
2240	2580	340	Dolomite, Limestone, Chert				
2580	3410	830	Dolomite				
3410	3600	190	Dolomite, Sandstone				
3600	4060	460	Dolomite				
4060	5180	1120	Shale, Do.omite				
5180	6520	1340	Limestone, Shale				
6520	6750	230	Lime, Shale, Sand				
6750	8090	1340	Lime, Shale				
8090	8320	230	Lime, Shale, Chert				
8320	8470	150	Sand, Lime, Shale				
8470	8635	165	Shale, Limestone				