

ckf

NM OIL CONS. COMMISSION
DEPT. OF THE INTERIOR
GEOLOGICAL SURVEY

Form 9-331
Dec. 1973

Form Approved
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR
Premier Production Co.

3. ADDRESS OF OPERATOR
324 West Main Artesia, N.M.

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 330' FSL 2310' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:
TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Plug & Abandon

SUBSEQUENT REPORT OF:
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED BY
DEC 12 1985
O. C. D.
ARTESIA OFFICE

5. LEASE	NM 17223
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME	Pogo Federal
9. WELL NO.	1
10. FIELD OR WILDCAT NAME	Turkey Track SR, Q, GB, SA.
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	SEC: 26 T-18-S R-29-E
12. COUNTY OR PARISH	13. STATE New Mex.
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD)	3483' 3418' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

We propose to plug and abandon this Well as follows: Tag cast iron bridge plug at 2900' w/ Tubing open ended, Pump 50 Sax cement (500' plug) 2900-2400' pull out tubing & tag plug; Pump 50 sax cement (500' plug) 2400' - 1900' pull out tubing & tag plug; pump 50 sax cement (500' Plug) 1900' - 1400' pull out tubing & tag plug; Pump 100' cement plug 1000'-900' to isolate the bottom of salt; Pump 100' cement plug 385'- 285'; isolate surface casing & top of salt; set 50' cement plug at surface; cut off well head and install 4"x4" dry-hole marker. Back Fill pits and Clean up location.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Henry Jones TITLE operator DATE 12-5-85

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE 12-11-85
CONDITIONS OF APPROVAL, IF ANY: