

Form 1001
(May 1983)

RECEIVED BY

APR -3 1985

O.C.D.

ARTESIA, OFFICE

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use APPLICATION FOR PERMIT for such proposals.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Collier Energy, Inc.

3. ADDRESS OF OPERATOR

P.O. Drawer R, Artesia, New Mexico 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1650' FSL & 1770 FWL of Section

(Unit K)
(NE $\frac{1}{4}$ SW $\frac{1}{4}$)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3593-GR

5. LEASE DESIGNATION AND SERIAL NO.

NM-42410

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Comstock Federal

9. WELL NO.

#2

10. FIELD AND POOL OR WILDCAT

Artesia Oil Pool

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 12-18S-27-E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐
☐

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) surface casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐
☐
☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3/16/85 Well was spudded at 9:15 am with 12 $\frac{1}{4}$ " hole.

Ran 376' of 8 5/8", 24# J-55 surface casing.

Cemented with 350 sks Class "C", 2% CaCl, $\frac{1}{4}$ # flocele

Plug down at 9:30 pm

Pressure tested 1000# for 30 min. - Held fine.

Circulated 92 sks to pit.

WOC 18 hours.

18. I hereby certify that the foregoing is true and correct

SIGNED Dickie Sue

TITLE Production Clerk

DATE 3/29/85

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY [Signature]
CONDITIONS OF APPROVAL, [Signature]

TITLE _____

DATE _____

APR 2 1985

*See Instructions on Reverse Side

CARLSBAD, NEW MEXICO