

Drawer DD

Artesia, New Mexico
SUMMIT 18256
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.Form 5-331
(May 1983)RECEIVED BY
MAY 2 1985UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYOCS
SURFACEDRY NOTICES AND REPORTS ON WELLS(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Collier Energy, Inc. ✓

3. ADDRESS OF OPERATOR

P.O. Drawer R, Artesia, New Mexico 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

330' FSL & 2310' FEL of Section

(Unit 0)

(SW $\frac{1}{4}$ SE $\frac{1}{4}$)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3589 GR

5. LEASE DESIGNATION AND SERIAL NO.

NM-42410

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

White Oaks Federal

9. WELL NO.

#1

10. FIELD AND POOL, OR WILDCAT

Artesia Oil Pool

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 12: T-18-S, R-27-E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐PULL OR ALTER CASING ☐FRACTURE TREAT ☐MULTIPLE COMPLETE ☐SHOOT OR ACIDIZE ☐ABANDON* ☐REPAIR WELL ☐CHANGE PLANS ☐(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐REPAIRING WELL ☐FRACTURE TREATMENT ☐ALTERING CASING ☐SHOOTING OR ACIDIZING ☐ABANDONMENT* ☐(Other) surface casing ☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/19/85 Spudded surface with 12 $\frac{1}{4}$ " bit at 11:15 am

Ran 357' of 8 5/8", 24# API, J-55 casing

Cemented with 275 sks Class "C", 2% CaCl, $\frac{1}{4}$ # flocele

Plug down at 10:30 pm

Pressure tested 1000# for 30 minutes - Held fine

Circulated 20 sks to surface

WOC 18 hours.



18. I hereby certify that the foregoing is true and correct

SIGNED Wiskie DealTITLE Production ClerkDATE 4/25/85

(This space for Federal or State office use)

APPROVED BY ACCEPTED FOR RECORD
CONDITIONS OF APPROVAL, IF ANY APR 29 1985

TITLE

DATE

*See Instructions on Reverse Side

CARLSBAD, NEW MEXICO