merly 9-331) DE	UN D STATES ARTMENT OF THE INTERI	Drauber instructions	Expires August 31, 1985 5. LEASE DESIGNATION AND SERIA	
	UREAU OF LAND MANAGEMENT	CAFTESIA, NM 88210	LC 062029	
APR -3 1985 SUNDRY	NOTICES AND REPORTS (	ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE	NAME
On not wy, this form f	or proposals to drill or to deepen or plug b APPLICATION FOR PERMIT-" for such pu	roposals.)	7. UNIT AGREEMENT NAME	
WELL X GAS WELL	07H EB		8. FARM OR LEASE NAME	
NAME OF OPERATOR			Roadrunner Federal	
MYCO Industri	les, Inc.		9. WBLL NO.	
207 South 4th	n St., Artesia, NM 88210		2	
LOCATION OF WELL (Report See also space 17 below.) At surface	ocation clearly and in accordance with any		10. FIELD AND POOL, OR WILDCAT South Leo, 7 Riv. Of Grayburg, San Andre 11. SHC, T. T., M., OR BLE. AND	ueen-
2310 F	NL & 2310 FWL, Sec. 35-T18	S-R29E	BUEVET OR AREA	
			Unit F, Sec. 35-T1	
. PERMIT NO.	15. ELEVATIONS (Show whether DF	7, MT, GR, CCC.)		
	3422' GR			NM
C	neck Appropriate Box To Indicate N			
NOTICE	OF INTENTION TO:	SUBS	EQUENT REPORT OF:	
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	X REPAIRING WELL	
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING	
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING		
				1
Spudded 12-1/4" 1-guide shoe set w/1/4#/sx cello	CHANGE PLANS LETED OPERATIONS (Clearly state all pertinent is directionally drilled, give subsurface loca hole at 5:45 PM 3-24-85. t 338'. Insert float set seal + 3% CaCl2. Tailed i at - 1250 psi in 12 hrs	Ran 8 joints 8-5/8 296'. Cemented w/7 n w/75 sx Class "C"	" 24# J-55 casing set( 5 sacks Pacesetter Lit w/2% CaCl2. Compressi	338'). e ve
(Other) DESCRIBE PROPOSED OR COMP proposed work. If well nent to this work)* Spudded 12-1/4" 1-guide shoe set w/1/4#/sx cellos strength of cemen released pressu Temperature Surrout out 4:30 PM 3-2.	LETED OPERATIONS (Clearly state all pertinent is directionally drilled, give subsurface loca t 338'. Insert float set seal + 3% CaCl2. Tailed i nt - 1250 psi in 12 hrs. re and float held okay. C vey and found top of cemen 5-85. WOC 12 hrs. NU and	(Nors: Report rest Completion or Reco at details. and give pertinent da ktions and measured and true ver Ran 8 joints 8-5/8 296'. Cemented w/7 n w/75 sx Class "C" PD 4:30 AM 3-25-85. ement did not circu t 75'. Ready-mix t tested to 1000 psi	<pre>mpletion Report and Log form.) tes, including estimated date of start ritical depths for all markers and gon 24# J-55 casing set( 5 sacks Pacesetter Lit w/2% CaCl2. Compressi Bumped plug to 1000 late. WOC 6 hrs. Ran o surface. WOC. Dril</pre>	338). e ve psi,
(Other) DESCRIBE PROPOSED OR COMP proposed work. If well nent to this work)* Spudded 12-1/4" 1-guide shoe set w/1/4#/sx cellos strength of cement released pressur Temperature Sur- out 4:30 PM 3-2.	LETED OPERATIONS (Clearly state all pertinent is directionally drilled, give subsurface loca hole at 5:45 PM 3-24-85. t 338'. Insert float set seal + 3% CaCl2. Tailed i nt - 1250 psi in 12 hrs. re and float held okay. C yey and found top of cemen	(Nors: Report rest Completion or Reco at details. and give pertinent da ktions and measured and true ver Ran 8 joints 8-5/8 296'. Cemented w/7 n w/75 sx Class "C" PD 4:30 AM 3-25-85. ement did not circu t 75'. Ready-mix t tested to 1000 psi	<pre>mpletion Report and Log form.) tes, including estimated date of start ritical depths for all markers and gon 24# J-55 casing set( 5 sacks Pacesetter Lit w/2% CaCl2. Compressi Bumped plug to 1000 late. WOC 6 hrs. Ran o surface. WOC. Dril</pre>	338'. e ve psi, led
(Other) DESCRIBE INDPOSED OR COMP proposed work. If well nent to this work)* Spudded 12-1/4" 1-guide shoe set w/1/4#/sx cellor strength of cement released pressur Temperature Surrout 4:30 PM 3-22 Reduced hole to	LETED OPERATIONS (Clearly state all pertinent is directionally drilled, give subsurface loca hole at 5:45 PM 3-24-85. t 338'. Insert float set seal + 3% CaCl2. Tailed i nt - 1250 psi in 12 hrs. re and float held okay. C vey and found top of cemen 5-85. WOC 12 hrs. NU and 7-7/8". Drilled plug and	(Nors: Report rest Completion or Reco at details. and give pertinent da tions and measured and true ver Ran 8 joints 8-5/8 296'. Cemented w/7 n w/75 sx Class "C" PD 4:30 AM 3-25-85. ement did not circu t 75'. Ready-mix t tested to 1000 psi resumed drilling.	mpletion Report and Log form.) tes, including estimated date of start tical depths for all markers and gon 24# J-55 casing set 5 sacks Pacesetter Lit w/2% CaCl2. Compressi Bumped plug to 1000 1ate. WOC 6 hrs. Ran o surface. WOC. Dril for 30 minutes, OK. ARD MARY More	338". e ve psi, led
(Other) DESCRIBE INDPOSED OR COMP proposed work. If well nent to this work)* Spudded 12-1/4" 1-guide shoe set w/1/4#/sx cellor strength of cement released pressur Temperature Surrout 4:30 PM 3-22 Reduced hole to	LETED OPERATIONS (Clearly state all pertinent is directionally drilled, give subsurface loca hole at 5:45 PM 3-24-85. t 338'. Insert float set seal + 3% CaCl2. Tailed i nt - 1250 psi in 12 hrs. re and float held okay. C vey and found top of cemen 5-85. WOC 12 hrs. NU and 7-7/8". Drilled plug and	(Nors: Report rest Completion or Reco at details. and give pertinent da ktions and measured and true ver Ran 8 joints 8-5/8 296'. Cemented w/7 n w/75 sx Class "C" PD 4:30 AM 3-25-85. ement did not circu t 75'. Ready-mix t tested to 1000 psi	mpletion Report and Log form.) tes, including estimated date of start tical depths for all markers and gon 24# J-55 casing set 5 sacks Pacesetter Lit w/2% CaCl2. Compressi Bumped plug to 1000 1ate. WOC 6 hrs. Ran o surface. WOC. Dril for 30 minutes, OK. ARD MARY More	338". e ve psi, led
(Other) DESCRIBE PROPOSED OR COMP proposed work. If well nent to this work.)* Spudded 12-1/4" 1-guide shoe set w/1/4#/sx cellos strength of cemen released pressu Temperature Sur- out 4:30 PM 3-2. Reduced hole to 8. I hereby certify that the f SIGNER (This space for Federal or	LETED OPERATIONS (Clearly state all pertinent is directionally drilled, give subsurface loca hole at 5:45 PM 3-24-85. t 338'. Insert float set seal + 3% CaCl2. Tailed i nt - 1250 psi in 12 hrs. re and float held okay. C vey and found top of cemen 5-85. WOC 12 hrs. NU and 7-7/8". Drilled plug and 7-7/8". Drilled plug and	(Nors: Report rest Completion or Reco at details. and give pertinent da tions and measured and true ver Ran 8 joints 8-5/8 296'. Cemented w/7 n w/75 sx Class "C" PD 4:30 AM 3-25-85. ement did not circu t 75'. Ready-mix t tested to 1000 psi resumed drilling.	mapletion Report and Log form.) tes, including estimated date of start ritical depths for all markers and gon " 24# J-55 casing set 5 sacks Pacesetter Lit w/2% CaCl2. Compressi Bumped plug to 1000 late. WOC 6 hrs. Ran o surface. WOC. Dril for 30 minutes, OK.	338". e ve psi, led
(Other) DESCRIBE PROPOSED OR COMP proposed work. If well nent to this work.)* Spudded 12-1/4" 1-guide shoe set w/1/4#/sx cellos strength of cemen released pressu Temperature Sur- out 4:30 PM 3-2. Reduced hole to 8. I hereby certify that the f SIGNER (This space for Federal or	LETED OPERATIONS (Clearly state all pertinent is directionally drilled, give subsurface loca hole at 5:45 PM 3-24-85. t 338'. Insert float set seal + 3% CaCl2. Tailed i nt - 1250 psi in 12 hrs. re and float held okay. C vey and found top of cemen 5-85. WOC 12 hrs. NU and 7-7/8". Drilled plug and 7-7/8". Drilled plug and oregoing is true and correct to the product of the period State office use) TED FOR RECORD	(Nors: Report rest Completion or Reco at details. and give pertinent da tions and measured and true ver Ran 8 joints 8-5/8 296'. Cemented w/7 n w/75 sx Class "C" PD 4:30 AM 3-25-85. ement did not circu t 75'. Ready-mix t tested to 1000 psi resumed drilling.	mpletion Report and Log form.) tes, including estimated date of start tical depths for all markers and gon 24# J-55 casing set 5 sacks Pacesetter Lit w/2% CaCl2. Compressi Bumped plug to 1000 1ate. WOC 6 hrs. Ran o surface. WOC. Dril for 30 minutes, OK. ARD MARY More	338". e ve psi, led
(Other) DESCRIBE INDPOSED OR COMP proposed work. If well nent to this work.)* Spudded 12-1/4" 1-guide shoe set w/1/4#/sx cellor strength of cemen released pressu Temperature Surrout 4:30 PM 3-22 Reduced hole to 8. I hereby cirtly that the f SIGNER (This space for Federal on ACCE APPROVED BY CONDITIONS OF APPRO	LETED OPERATIONS (Clearly state all pertinent is directionally drilled, give subsurface loca hole at 5:45 PM 3-24-85. t 338'. Insert float set seal + 3% CaCl2. Tailed i nt - 1250 psi in 12 hrs. re and float held okay. C vey and found top of cemen 5-85. WOC 12 hrs. NU and 7-7/8". Drilled plug and 7-7/8". Drilled plug and oregoing is true and correct to the product of the period State office use) TED FOR RECORD	(Nors: Report rest Completion or Reco at details. and give pertinent da tions and measured and true ver Ran 8 joints 8-5/8 296'. Cemented w/7 n w/75 sx Class "C" PD 4:30 AM 3-25-85. ement did not circu t 75'. Ready-mix t tested to 1000 psi resumed drilling.	mapletion Report and Log form.) tes, including estimated date of start ritical depths for all markers and gon " 24# J-55 casing set 5 sacks Pacesetter Lit w/2% CaCl2. Compressi Bumped plug to 1000 late. WOC 6 hrs. Ran o surface. WOC. Dril for 30 minutes, OK.	338". e ve psi, led

~

Title 18 U.S.C. Section T001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.