

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIP. (TE)
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC 062029

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Roadrunner Federal

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT
South Leo, 7 Rivers-Q-
Grayburg SA

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Unit F, Sec. 35-T18S-R29E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3422' GR

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Production Casing, Perforate

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-31-85. TD 3210'. Ran 77 joints 5-1/2" 15.5# J-55 casing set 3210'. 1-guide shoe set : 3210'. Float set 3168'. Cemented w/250 sx Pacesetter Lite w/7#/sack salt, 1/4#/sack celloseal. Tailed in w/550 sx Class "C" w/.6% CF-1, .2% AFS and 5#/sack salt. Compressive strength of cement - 950 psi in 12 hrs. PD 10:35 AM 3-31-85. Bumped plug to 1000 psi - released pressure, float and casing held okay. Cement circulated 50 sacks. WOC.

4-12-85. WIH and perforated 2733-45' and 2782-85' w/11 .42" holes as follows: 2733, 34, 35, 36, 43, 44 and 45' (7 holes); 2782, 83, 84 and 85' (4 holes). Acidized perfs 2782-85' w/500 gals 7½% NEFE acid and 3 ball sealers.

4-13-85. Acidized perfs 2733-45' w/750 gals 15% NEFE acid plus 6 ball sealers.

4-15-85. WIH and perforated 2790-2809' w/7 .42" holes as follows: 2790, 96, 97, 2802½, 07, 08, and 09'. Acidized zone w/1500 gals 15% NEFE acid. Frac'd perforations 2733-2809' w/30000 gals gelled water and 56000# 20/40 sand.

RECEIVED BY

APR 23 1985

O. C. D.

ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Production Supervisor

DATE 4-16-85

(This space for Federal or State office use)

APPROVED BY ACCEPTED FOR RECORD

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APR 17 1985

*See Instructions on Reverse Side