

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

MAR 11 1993

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

MYCO INDUSTRIES, INC. ✓

3. Address and Telephone No.

P.O. BOX 840 ARTESIA, NM. 88211-0840 505-748-1471

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2310' FNL & 2310' FWL SEC. 35 T18s-R29e UNIT F

5. Lease Designation and Serial No.
LC-062029

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

ROADRUNNER FEDERAL # 2

9. API Well No.

30-015-25216

10. Field and Pool, or Exploratory Area

TURKEY TRACK SR-Q-G-SA

11. County or Parish, State

EDDY, NM.

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 3210' PBD 2638' 8 5/8"-338'- CEMTD TO SURFACE, 5 1/2" -3200'- CIRC.
PERFORATIONS 2533'-2536' & 2558'-2588'

PLUGGED AND ABANDONED AS FOLLOWS PER FORM 3160-5 APPROVED 2/4/93

3/3/93 CARLOS GUERRERO NOTIFIED JIM AMOS BLM OF P&A. BLM WITNESS KATHY QUEEN

3/4/93

A-- SET A CIBP @ 2498' & CAPPED W/ 15 SKS CEMENT

B-- PUMPED A 25 SK CEMENT PLUG @ 1050'

C-- PUMPED A 25 SK CEMENT PLUG @ 400'

D-- PUMPED A 15 SK CEMENT PLUG @ 51' TO SURFACE

E-- SET REGULATION DRY HOLE MARKER

NCTE: LOADED HOLE AND DISPLACED ALL PLUGS W/(9.0 # PG MIN) MUD.

F-- WILL NOTIFY WHEN READY FOR FINAL INSPECTION.

Post ID-2
4-9-93
P&A

MAR 12 10 47 AM '93
CAB AREA

RECEIVED

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed W. A. Gressett

Title CONSULTANT

Date 3/11/93

(This space for Federal or State office use)

Approved by (ORIG. SGD.) DAVID R. GLASS

Title

Date MAR 19 1993

Conditions of approval, if any: