

NEW MEXICO OIL CONSERVATION COMMISSION

DRAWER DE
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator HES OILCO		Lease INEX		Well # 1	
Location of Well	Unit H	Section 26	Township 18	Range 26	County EDDY
Drilling Contractor	AFT		Type of Equipment ROTARY		

* = CSG. TO WITNESS

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cemen

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
 _____ (Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 550

Type of Shoe used GUIDE Float collar used none Btm 3 jts welded YES

TD of hole 981 Set 981 Feet of 8 5/8 inch 24 # Grade J-55

(New) used csg. @ 981 with 150 sacks neat cement around shoe + 2% $CaCl_2$
 + 400 sack High Density additives 1/4" x 9/16" gills, 1/4" x 3/8" pebbles, 2% $CaCl_2$

Plug down @ 7:58 (AM) (PM) Date 6/27/85

Cement circulated YES No. of Sacks 70 Sxs.

Cemented by DOWELL Witnessed by Randy Brooks

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____