

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Exp. 1-17-86

Operator <u>Yates Petr. Corp.</u>		Lease <u>Boykin "ACV" Com</u>		Well # <u>1</u>	
Location of Well	Unit <u>D</u>	Section <u>34</u>	Township <u>18</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor <u>La Rue Drllg.</u>			Type of Equipment <u>Rotary</u>		

* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>12 1/4</u>	* <u>8 5/8</u>	<u>24# K-55</u>		<u>940</u>	<u>400 Circ</u>
<u>7 7/8</u>	<u>5 1/2</u>	<u>14# K-55</u>		<u>TD</u>	<u>500 Circ</u>

Casing Data:

Surface 23 joints of 8 5/8 inch 24 # Grade J-55

Yes (Approved) (Rejected) 7-23-85

Inspected by BW Weaver date

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 150

Type of Shoe used Tex-At Float collar used Insert Btm 3 jts welded Yes

TD of hole 918 Set 918 Feet of 8 5/8 Inch 24 # Grade J-55

New-used csg. @ 918 with 150 sacks neat cement around shoe

+ 300 sax Pace Setter lite additives 3% CC

Plug down @ 11:30 (AM) (PM) Date 7-23-85

Cement circulated NO No. of Sacks

Cemented by Western Witnessed by BW Weaver

Temp. Survey ran @ 6:00 (AM) (PM) Date 7-24-85 top cement @ 150

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Last drilling Break 803 Ft

Ran 1" to 150 Ft and circulated Cement to 142 100 SX Class 2 Cement