

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

1-31-86

Operator	H&S OIL CO.		Lease	WILLIAMS		Well #	14
Location of Well	Unit	Section	Township	Range	County		
	C	25	18	26	EDDY		
Drilling Contractor	AFT		Type of Equipment				
			ROTARY				

* = CSG. TO WITNESS

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
* 12 1/4	8 5/8	24	NEW	960'	circ [700]
7 7/8	5 1/2	15	"	3670	670'

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 600 Jx.

Type of Shoe used GULF Float collar used INST. Btm 3 jts welded YES

ID of hole 980 Set 975' Feet of 8 5/8 Inch 24 # Grade J-55

New used csg. @ 975' with 200 sacks neat cement around shoe c.i.c 2% CaCl₂
+ 400 sax DOWELL LITENGT additives + 1/4#/sk celloflake.

Plug down @ 5:30 (AM) (PM) Date 8/3/85

Cement circulated YES No. of Sacks 70

Cemented by DOWELL Witnessed by Larry Brooks

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: LAST DRILLING BREAK AT 880' LB.