

GAS-OIL RATIO TESTS

H&S Oil Company		Atoka, Glorieta Yeso		Eddy										
Suite 303, First National Bank Bldg., Artesia, N.M. 88210		TYPE OF TEST - (X)		Sample used										
LEASE NAME	WELL NO.	LOCATION			DATE OF TEST	CHOKE SIZE	TBG. PRESS.	DAILY ALLOWABLE	LENGTH OF TEST HOURS	PROD. DURING TEST			GAS-OIL RATIO	
		U	S	T						R	WATER BBLs.	GRAV. OIL		OIL BBLs.
Inex	2	H	26	18	26	3/5/86	P	30	24	178	36	30	40	1330
Williams	✓15	D	25	18	26	3/5/86	P	30	24	210	36	30	45	1500

RECEIVED BY
MAR 25 1986
O. C. D.
ARTESIA OFFICE

No well will be assigned an allowable greater than the amount of oil produced on the official test.

During gas-oil ratio tests, each well shall be produced at a rate not exceeding the top unit allowable for the pool in which well is located by more than 25 percent. Operator is encouraged to take advantage of this 25 percent tolerance in order that well can be assigned increased allowables when authorized by the Commission.

Gas volumes must be reported in MC if measured at a pressure base of 15,025 psia and a temperature of 60° F. Specific gravity base will be 0.60.

Report casing pressure in lieu of tubing pressure for any well producing through casing.

Mail original and one copy of this report to the district office of the New Mexico Oil Conservation Commission in accordance with Rule 36, and after 10 days post report.

I hereby certify that the above information is true and complete and that I am duly qualified to make such and these.