

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED BY

JAN 21 1987

O. C. D.

ARTESIA OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR OFFICIAL ACTION. IT IS FOR INFORMATION ONLY. IT DOES NOT BACK TO A DIFFERENT RESERVOIR.
USE APPROPRIATE FORM FOR EACH TYPE OF ACTION.)

5a. Indicate Type of Lease

State ☒

Fee ☐

5. State Oil & Gas Lease No.

B-3823

7. Unit Agreement Name

6. Form or Lease Name

Walter S. 1

9. Well No.

1

10. Field and Pool, or Wildcat

Wildcat Penn

12. County

Eddy

1. OIL ☐ GAS ☐ OTHER ☐

2. Name of Operator

Frostman Oil Corporation ✓

3. Address of Operator

P. O. Drawer W, Artesia, NM 88210

4. Location of Well

UNIT LETTER L 400 FEET FROM THE West LINE AND 2240 FEET FROM

THE South LINE, SECTION 5 TOWNSHIP 18 S RANGE 28E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

OTHER ☐

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☐

CASING TEST AND CEMENT JOB ☐

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6/23/86: Shot off casing at 7846' with jet shot. Pulled casing out of hole.

6/25/86: Installed Halliburton packer shoe on bottom & Lynes casing formation packer 157' above bottom casing. Ran casing back to T.D. Packer shoe at 7832, Lynes packer at 7690. Dropped ball, loaded casing, broke circulation. Cemented with 100 Sxs of Class H Cement. Pumped plug down. Pressured casing to 3250'. Plug down 5:30 p.m. 6/25/86.

6/30/86: Ran bond log top of cement at 7400'. Perforated 7778' - 7787' (10 holes) acidized with 1000 gals of 15% acid. Swabbed all water.

7/2/86 : Perforated 7810'-7812' (1 shot per foot). Swabbed with packer at 7794' - all water.

7/3/86 : Perforated 7742' - 7756' (15 holes) Set bridge plug at 7768', packer at 7685', acidized with 1000 gal. 15% acid. Swabbed - all water.

7/9/86 : Perforated 7518' to 7534' (16 ft. - 17 holes). Acidized with 1000 gals. 15% acid. Swabbed - all water.

Set bridge plug at 7490', pulled tubing and shut in well.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

FROSTMAN OIL CORPORATION

SIGNED *Clarence Forister*

TITLE Clarence Forister, President

DATE 1/20/87

Original Signed By

Leslie A. Clements

Supervisor District II

TITLE

DATE

JAN 27 1987

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY