UNITED STATES: CIL CONSRIPHITATEN TRIPLICATES November 1983) (Formerly 9-331) DEPARTMEN OF THE INTERIOR (Other Inherence of the rece side) BUREAU OF LAND MANAGEMENT NM 88210 SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.) OIL		LC-029389 B 6 IF INDIAN, ALLOTTEE OR TRIBE NAME 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME Wilmar Federal					
				HONDO Oil and Gas Company 3. ADDRESS OF OPERATOR P. O. Box 1610, Midland, Texas 79702 4. LOCATION OF WELL (Report location clearly and in accordance w See also space 17 below.) At surface 560 FSL & 960 FWL (Unit Letter M)	OCT 27, 1986	Tamano (Bone 11. SEC., T., E., M., C SURVEY OR A	Springs) B BLE. AND
				15 ELEVATIONS (Show w	O. C. D. hether 17, RT. GRARZESIA, OFFICE	4-18S-31E 12. COUNTY OR PAR	l l
101# 20 0/5-22660 37050.0 GR		Eddy	NM				
16. Check Appropriate Box To Ind	icate Nature of Notice, Report, or	Other Data QUENT BBPORT OF:					
NOTICE OF INTENTION TO:	-7 -7		NG WELL				
TEST WATER SHUT-OFF FRACTURE TREAT NHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER UNSING MULTIPLE COMPLETE ABANDON® CHANGE FLANS	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) Intermediat	ALTERIN ABANDO	G CASING MENT* X Jon on Well				
(Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all proposed work. If well is directionally drilled, give subsurnent to this work.) TD'd 11" hole @ 2187' @ 1:45 a.m. 9-30-86. 8rd csg. Cmt'd @ 2187' w/880sx "C". Circ NU BOP. Test to 3000#. OK. Test csg to DNF 2:45 a.m. 10-1-86.	RIH w/54 jts 8-5/8", 24#, K-55 cmt to surface. WOC. Install	, STC,					
ACCEPTED FOR RE Sur OCT 24 198		23	1986 (1)				
		A Commence					
CARLSBAD, NEW MEXICO							
18. I hereby certify that the foregoing is true and correct	915-688-5672 ETLE Engr. Tech. Spec.	DATE	10-21-86				
SIGNED _ A Z V A Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z	TLE LIGIT TOOM OPEN						
(This space for Federal or State office use)		DATE					
APPROVED BYTI	ITLE						

*See Instructions on Reverse Side