

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-79

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	<input checked="" type="checkbox"/>
LAND OFFICE	<input checked="" type="checkbox"/>
OPERATOR	<input checked="" type="checkbox"/>

RECEIVED BY

NOV 13 1986

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR A WELL" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name Hoffman PL
3. Address of Operator 105 South 4th St., Artesia, NM 88210		9. Well No. 3
4. Location of Well UNIT LETTER <u>L</u> <u>1650</u> FEET FROM THE <u>South</u> LINE AND <u>330</u> FEET FROM THE <u>West</u> LINE, SECTION <u>27</u> TOWNSHIP <u>18S</u> RANGE <u>26E</u> NMPM.		10. Field and Pool, or WHdcat Atoka Glorieta Yeso
15. Elevation (Show whether DF, RT, GR, etc.) 3355' GR		12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER Perforate, Sand frac ☒

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1109.

11-4-86. Frac'd perforations 3077-3551' w/25000# 20/40 sand, 1000 gal. 15% NEFE, scale and corrosion inhibitor w/Parachek 140 + 55000# 20/40 + 60000# 12/20 sand in 80000 gal 35 ppg gel.
11-5-86. WIH and perforated 2551-2978' w/36 .42" holes as follows: 2551, 56, 63, 70, 76, 81, 86, 92, 2601, 07, 34, 40, 45, 49, 59, 63, 2622, 26, 32, 38, 43, 52, 56 (23 holes); 2782, 86, 90, 96, 2802, 55, 65, 69, 79, 2968, 71, 78' (13 holes. Treated perforations w/4100 gals 15% NEFE acid.
Frac'd perforations 2551-2978' w/ Parachek-140 in pad, 25000# 20/40 sand + 1000 gal 15% NEFE in scale and corrosion inhibitor, 55000# 20/40+ 60000# 12/20 in 80000 gals gelled KCL.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Les A. Clements

TITLE Production Supervisor

DATE 11-11-86

Original Signed By
Les A. Clements

APPROVED BY Supervisor District II

TITLE _____

DATE NOV 14 1986

CONDITIONS OF APPROVAL, IF ANY: