

## FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator <u>Gates Petr. Corp.</u>		Lease <u>Compromise</u> <u>AET Fed. Com</u>		Well # <u>1</u>	
Location of Well	Unit <u>H</u>	Section <u>30</u>	Township <u>18</u>	Range <u>27</u>	County <u>Eddy</u>
Drilling Contractor	<u>1980/N 800/E</u> <u>NA</u>		Type of Equipment <u>Rotary</u>		

**\* Witness** APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>13 3/8</u>	<u>48# H-40</u>		<u>375</u>	<u>500 Circ</u>
<u>12 1/4</u>	<b>*</b> <u>8 5/8</u>	<u>24# J-55</u>		<u>1300</u>	<u>1500 Circ</u>
<u>7 7/8</u>	<u>5 1/2</u>	<u>17# K-55</u> or <u>15.5# K-55</u>		<u>TD</u>	<u>300</u>

Casing Data:

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_  
(Approved) (Rejected) \_\_\_\_\_

Inspected by \_\_\_\_\_ date \_\_\_\_\_

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required \_\_\_\_\_

Type of Shoe used guide Float collar used insert Btm 3 jts welded yes

TD of hole 1248' Set 1248' Feet of 8 5/8" Inch 24 # Grade J-55

New-used csg. @ 1248' with 250 sacks neat cement around shoe  
+ 450 sax Hall. Lite additives (1/4# floreal, 290cc)

Plug down @ 7:30 (AM) (PM) Date 11/3/86

Cement circulated yes No. of Sacks 25

Cemented by Halliburton Witnessed by Mike Stullfield

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: \_\_\_\_\_

Full return to TD  
Last dily level @ 1140'