	SUBMIT IN TRIPLIC TE. ERIOR (Other instructions re- terior verse alde)	Budget Bureau No. 1004-0135 Expires August 31, 1985 5. LEASE DESIGNATION AND SERIAL NO
BUREAU OF LAND MANAGEM SUNDRY NOTICES AND REPORT (Do not use this form for proposals to drill or to deepen or p Use "APPLICATION FOR PERMIT_" for su	S ON WELLS	NM 65392 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
1.		7. UNIT AGREEMENT NAME
OIL GAS WELL OTHER	RECEIVED BY	
2. NAME OF OPERATOR Yates Petroleum Corporation	NOV	8. FARM OR LEASE NAME
3. ADDRESS OF OPERATUR	NOV 14 1986	Compromise AEJ Federal Com
105 South 4th St., Artesia, NM 88210	000	1
4. LOCATION OF WELL (Report location clearly and in accordance with See also space 17 below.)	a y State requirements.*	10. FIELD AND POOL, OR WILDCAT
At surface 1980' FNL & 800' FEL, Sec. 30-	T18C_D27E	Und. Best Lake Morrow 11. SBC., T., B., M., OR BLK. AND SUBVET OB ARKA
1900 IND & 000 IND, 500, 50-	-1103-K27E	Unit H, Sec. 30-T18S-R27E
14. PERMIT NO. 15. ELEVATIONS (Show wheth	er DF, RT, GR. etc.)	12. COUNTY OR PARISH 13. STATE
API #30-015-25665 3281' GR		Eddy NM
16. Check Appropriate Box To Indica	te Nature of Notice, Report, or C	Other Data
NOTICE OF INTENTION TO:		ENT REPORT OF :
TEST WATER SHUT-OFF	WATER SHUT-OFF	REPAIRING WELL
FRACTUBE TREAT MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE ABANDON*	SHOOTING OR ACIDIZING	ABANDON MENT*
REPAIR WELL CHANGE PLANS	(Other)	of multiple completion on Well
(Other) j 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Cleanly state all per proposed work. If well is directionally drilled, give subsurface	Completion or Recompl	etion Report and Log form.)
Spudded 26" hole at 7:50 PM 10-29-86. S Vince Balderaz, BLM, of spud. MIRT. Resumed drilling 17-1/2" hole 9:00 AM 11 set 398'. 1-Type M guide shoe set 398', Class "C" with 2% CaCl2. Compressive st 11:30 PM 11-1-86. Bumped plug to 500 ps Cement circulated 30 sacks. WOC. Drill and welded on flow nipple. Reduced hole ACCEPTED FOR RECO MOV 1 2 1986 CARLSBAD, NEW ME	-1-86. Ran 10 joints 13 insert float set 355'. rength of cement - 1250 si, released pressure and ed out 5:30 PM 11-2-86. to 12-1/4". Drilled pl	-3/8" 54.5# J-55 casing Cemented w/400 sacks psi in 12 hrs. PD float held okay. WOC 18 hrs. Cut off
18. I hereby certify that the foregoing is true and correct SIGNED CALLA TITLE (This space for Federal or State office use)	Production Supervisor	DATE4-86
APPROVED BY TITLE _ CONDITIONS OF APPROVAL, IF ANY:	· · · - · · · · · · · · · · · · · · · ·	DATE
CONDITIONS OF AFFRUVAL, IF ANI;		

*See Instructions on Reverse Side