

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instruction on re-
verse side)

1. Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

dsf

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR


Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

105 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' FNL & 800' FEL



14. PERMIT NO.

API #30-015-25665

15. ELEVATIONS (Show whether depth to top of casing or bottom of hole)

3281' GR

5. LEASE DESIGNATION AND SERIAL NO.

NM 65392

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Compromise AEJ Federal Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat Strawn

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit H, Sec. 30-T18S-R27E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Set CIBP, perforate, treat

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2-28-87 - MIPU. Pulled tubing and packer. Set CIBP at 9350' w/35' cement on top.

3-3-87 - WIH and perforated 8720-8725' w/10 .41" holes (2 SPF). Acidized perforations with 1500 gals 15% NEFE acid, 100# WB IIIIX Benzoic flakes.

Well cleaned up and flowed 115 psi on 1/2" choke = 795 mcfpd.

ACCEPTED FOR RECORD

MAR 12 1987

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Joyce Doodley

TITLE Production Supervisor

DATE 3-9-87

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side