

clsf

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill, to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR
Ray Westall

3. ADDRESS OF OPERATOR
Box 4 Loco Hills

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990' FNL & 560' FWL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other)	Spud, 13 3/8", 8 5/8", TD, 5 1/2"	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-17-86 Spud 17 1/2' hole @ 9:30 A.M.

11-22-86 Ran 13 jts., 427' of 13 3/8" 54 & 61# limited service casing. Cemented @ 427' w/160 sxs DWL#3, 200 sxs HE#2, circulated 87 sxs. Plug down @ 3:15 A.M. 11-22-86 WOC 18 hrs.

11-24-86 Ran 40 jts. 1623' of 8 5/8" 24# J-55 casing. Land & cement @ 1636' w/675 sxs DLW5, 4% gel, 5# salt, 200 sxs HE, 2% CaCl. Circulated 200 sxs. Plug down 2:30 P.M. 11-24-86. WOC 18 hrs. Pressured up BOP 1,000# for 30 min. Held OK.

11-29-86 T.D. @ 3456'. Ran 87 jts. 3480' 15.5# J-55 5 1/2" casing. Cemented @ 3456' w/680 sxs Tail in Standard, 3# salt, .5% D-59, .2% D-46. Plug down @ 8:30 P.M. 11-29-86. Rig released @ 9:00 P.M. 11-29-86.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ray Westall TITLE Operator DATE 12-02-86

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

Sud
DEC 2 1986

*See Instructions on Reverse Side

CARLSBAD, NEW MEXICO

