

C/SF

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR

Ray Westall

JAN 25 '88

3. ADDRESS OF OPERATOR

O. C. D.

ARTESIA OFFICE

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 990' FSL & 1650' FWL

AT TOP PROD. INTERVAL: same

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Spud, 13 3/8", 8 5/8", 5 1/2", T.D.

5. LEASE

NM-06245

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Trigg Federal

9. WELL NO.

5

10. FIELD OR WILDCAT NAME

Shugart - Y-56-2-4

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 35, T-18-S, R-30-E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3438 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED

JAN 19 10 56 AM '88

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-04-88 Spud 17 1/2" hole @ 4:30 PM

1-05-88 Ran 13 jts. 563' 13 3/8" 61 & 68# 8-RD ST&C R-3 Casing. Set and cement @ 558' w/320 sxs Class A 6% gel 1/4 lb. D29, 2% Sl and 200 sxs Class C 1% gel 1/4 lb. D29, 2% Sl - 1 Load Ready Mix-

1-07-88 Ran 38 jts. 1710' 24 & 28# 8 5/8" casing. Set and cement @ 1723' w/600 sxs 65/35 A Poz. mix 6% gel 1/4 lb. Flocele, 8# salt and 200 sxs HE-2, 1/4# Flocele, 2% CaCl. Circulate 75 sxs. WOC

1-12-88 TD @ 3612'. Ran 86 jts. 3598' 17# 5 1/2" csg. Cement top 1400' w/ 290 sxs Tool end Class A and 50 xsx Lite.. Plug Down @ 3:20 PM

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Mickelle Taylor TITLE Secretary DATE 1-13-88

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

SJS