

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

18. (Other instructions
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

45F

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. NAME OF OPERATOR
Manzano Oil Corporation ✓ 505/623-1996
3. ADDRESS OF OPERATOR
P.O. Box 2107/Roswell, NM 88202-2107
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
760' FSL & 2080' FEL (Unit Letter O)

RECEIVED

JUN 28 '88

O.C.D.
ARTESIAN OFFICE

5. LEASE DESIGNATION AND SERIAL NO.

NM-27279

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Elliott Federal

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

Santo-Nino-Bone Spring

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 30-T18S-R30E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

14. PERMIT NO.

30-015-25909

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3441 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Casing & Cementing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6/4/88 Spudded 17-1/2" hole @ 3:00 p.m. 6/4/88.

6/5/88 Drilled to 405'. Ran 10 joints (405.54') of 13-3/8" ST&C J-55 54.5# 8 rd casing with guide shoe & insert float. Set and cemented @ 405' w/400 sacks Class C with 2% CaCl. Plug down @ 12:30 a.m. 6/5/88. Did not circulate. Cemented thru 1" with 400 sacks Class C with 3% CaCl. Circulated 10 sacks.

6/8/88 Drilled 12 1/4" hole to 2076'. Ran 52 joints (2078.11') of 8-5/8" 24# ST&C J-55 8 rnd casing with guide shoe, float collar & 3 centralizers. Set & cemented @ 2076' with 800 sacks Halliburton Lite w/15# salt, 1/4# floseal per sack and 200 sacks Class C w/2% CaCl. Plug down @ 6:45 p.m. 6/8/88. Did not circulate. Ran 1" and cemented with 375 sacks Class C with 3% CaCl. Circulated 25 sacks to surface. Cement top 518'.

RECEIVED
JUN 28 1 41 PM '88

RECEIVED

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Jackie Midkiff/Landwoman

DATE 6/10/88

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUN 28 1988

*See Instructions on Reverse Side

SJS
CARLEAD, BLM, 1000-0