

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse)

RECEIVED

45F
Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO
NM-33437

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

PMS 8 Federal

9. WELL NO.

#2

10. FIELD AND POOL, OR WILDCAT

N. Shugart Bone Spring

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 8, T18S, R31E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back for different purposes.)
Use "APPLICATION FOR PERMIT—" for such proposals.

1. WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Harvey E. Yates Company

3. ADDRESS OF OPERATOR

P.O. Box 1933, Roswell, New Mexico 88202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below

660' FNL & 1650' FWL

14. PHONE NO.

30-015-26360

15. ELEVATIONS (Show whether DE, RT, GR, etc.)

3692.1

GEARTESIA OFFICE

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO

TEST WATER SHUT-OFF

FRAC TREATMENT

SHOOTING OR ACIDIZING

ABANDONMENT

OTHER

DRILL OR ALTER CASING

RE-DEPTH COMPLETE

ABANDON

CHANGE LEASE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRAC TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT

Spud, Surface & Int csg reports

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. (If well is being drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1/31/89 Spud well @ 2:30 pm, TD 17 1/2 hole @ 370 ft,
Ran 13 3/8 csg to 370 ft.
Cmtd w/375 sks "C" w/2% CaCl, TOC @ 15 ft, Pumped 65 sks "C"
w/2% CaCl & Circ 18 sks, WOC 12 hrs, Test BOP 600 psi/30 min-Held OK

2/3/89 TD 12 1/4" hole @ 2065ft, Ran 8 5/8 csg to 2065 ft,
Cmtd w/1100 sks filler & 200 sks "C" w/2% CaCl, Circ 340 sks,
WOC 12 hrs, Test BOP 1200 psi/30 min-Held OK

18. I hereby certify that the foregoing is true and correct

SIGNED

NM Young

TITLE

Drilling Superintendent

DATE

2/6/89

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

FEB 11 1989

*See Instructions on Reverse Side

SJS
CAR SRAD, NEW MEXICO