

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator <u>Gates Petr. Corp.</u>		Lease <u>Pierre ACF St. Conn</u>		Well # <u>1</u>	
Location of Well	Unit <u>A</u>	Section <u>26</u>	Township <u>18</u>	Range <u>27</u>	County <u>Eddy</u>
Drilling Contractor	<u>Undesignated</u>		Type of Equipment <u>Rotary</u>		

*** Witness** APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>* 13 3/8</u>	<u>40# K-55</u>		<u>250</u>	<u>300 Circ</u>
<u>12 1/4</u>	<u>* 8 5/8</u>	<u>24 + 32# K-55</u>		<u>2200</u>	<u>900 Circ</u>
<u>7 7/8</u>	<u>5 1/2</u>	<u>17# N-80 + S-95</u>		<u>TD</u>	<u>600</u>

Casing Data:

Surface 8 joints of 13 3/8 inch 54.5 # Grade J55

Approved (Approved) (Rejected)

Inspected by Johnny Rolinson date 3-6-89

Cementing Program

Size of hole 17 1/2 Size of Casing 13 3/8 Sacks cement required 325

Type of Shoe used guide Float collar used yes Btm 3 jts welded yes

TD of hole 324' Set 352 Feet of 13 3/8 inch 54.5 # Grade J55

New used csg. @ 324 with 325 sacks neat cement around shoe

+ sax additives

Plug down @ 8:06 (AM) (PM) Date 3-6-89

Cement circulated NO No. of Sacks

Cemented by Western Co Witnessed by Johnny Rolinson

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks:

1. Ran 1" + Tagged Top @ 260' w/ 135 sk C.I.C. 320cc

2. Ran 1" + Tagged Top @ 306' w/ 250 sk C.I.C. 320cc

cement circulated To surface. M.S.