

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87501-2088

MAR 13 '89

WELL API NO.

30-015-26065

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

B-110831

7. Lease Name or Unit Agreement Name

Pierre AGF State Com

8. Well No.

1

9. Pool name or Wildcat

Und. Red Lake Atoka-Morrow

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter A : 660 Feet From The North Line and 660 Feet From The East Line

Section 26 Township 18S Range 27E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3531.2' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 9:20 AM 2-28-89 with Auger Air. Set 40' of 20" conductor. Redi-mix to surface with 2-3/4 yards. Notified Carol Winters, NMOCD, Artesia, NM, of spud.

Lost returns 274. Dry drilled to 324'. Ran 8 joints 13-3/8" J-55 ST&C casing, set 324'. Texas Pattern Notched guide shoe set 324', insert float set 282'. Cemented w/325 sx Class "C" + 2% CaCl2 (yield 1.32, weight 14.8). PD 8:00AM 3-6-89. Bumped plug to 500 psi, released pressure and float held okay. Cement did not circulate. WOC 4 hrs. Ran 1". Tag cement 260'. Spotted 35 sx Class "C" + 4% CaCl2. PD 12:30 PM 3-6-89. WOC 1-1/2 hrs. Ran 1". Tag cement 206'. Spotted 250 sx Class "C" + 2% CaCl2. PD 3:00 PM 3-6-89. Circulated 10 sx to pit. WOC.

Drilled out 8:00 AM 3-7-89. WOC 24 hrs. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 12-1/4'. Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 3-9-89

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

Original Signed By
Mike Williams

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

MAR 13 1989