Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

RECEI	VED			
Ω	CONCED	VATIO	NDIX	TCION

Form C-103
Revised 1-1-89

MAR 1 7 1989

District Office	KECEIVED		,			
DISTRICT I P.O. Box 1980, Hobbs, NM 88240	OIL CONSERVATIO		WELL API NO.			
	P.O. Box 2088 MAR 15arl 89 e, New Mexico 87504-2088		30-015-26065			
DISTRICT II P.O. Drawer DD, Artesia, NM 88210	5. Indicate Type of Lease STATE X FEE					
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410	O. C. D. Artesia, Office	6. State Oil & Gas Lease No. B-110831				
CUNDRY NOT	ICES AND REPORTS ON WEL	1 0				
(DO NOT USE THIS FORM FOR PR DIFFERENT RESE (FORM (7. Lease Name or Unit Agreement Name					
1. Type of Well: OIL GAS WELL GAS	ОТНЕЯ		Pierre AGF State Com			
2. Name of Operator YATES PETROLEUM CORPOR	8. Well No.					
3. Address of Operator			9. Pool name or Wildcat			
105 South 4th St., Art	tesia, NM 88210		Und. Red Lake-Atoka-Morrow			
4. Well Location Unit Letter A :660	Feet From The North	Line and660	Feet From The East Line			
Section 26	Township 18S Ra	nge 27E	NMPM Eddy County			
Section 26 Township 185 Range 27E NMPM Eddy County						
3531.2' GR						
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data						
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:						
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING			
TEMPORARILY ABANDON	G OPNS. PLUG AND ABANDONMENT					
PULL OR ALTER CASING	EMENT JOB .					
OTHER:		OTHER: Interm	ediate Casing X			
12. Describe Proposed or Completed Oper work) SEE RULE 1103.	ations (Clearly state all pertinent details, an	nd give pertinent dates, incli	uding estimated date of starting any proposed			
shoe set 2200', inser 1/4#/sx Celloseal and with 2% CaCl2 (yield released pressure and 3-10-89. Bumped plug to pit. Drilled out 10:30 PM	ot float set 2158'. Cen 3% Gilsonite (yield 1.9 1.98, weight 14.8). PI d float held okay. Circ g to 1750 psi, released	nented w/900 sx 98, weight 12.4 0 3:15 AM 3-10- culated 50 sack pressure and f	as Pattern Notched guide Pacesetter Lite, 3% CaCl,). Tailed in w/250 sx Class C 89. Bumped plug to 1750 psi, s to pit. Drilled out 10:30 PM loat held okay. Circulated 50 sx NU and tested to 1000 psi for			
I hereby certify that the information above is to	ne filld complete to the best of my knowledge and	belief.				
Production Supervisor 3-13-89						
Juani	ta Goodlett	LE	TELEPHONE NO. 505/748-14			
TYPE OR PRINT NAME JUSTILL	ta doduictt		112211010101010077.10 211			

TITLE -

Original Signed By Mike Williams

(This space for State Use)

APPROVED BY-