				-151
			RECEILD	617.
Form 3160-5 (June 1990)	DEPARTME	ITED STATES NT OF THE INTERIOR	MAR 1 1 1991	FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993
BUREAU OF			O. C. D.	5. Lease Designation and Serial No.
		AND REPORTS ON WE	ARTESIA, OFFICE	NM 62588 6. If Indian, Allottee or Tribe Name
Do not use	this form for proposals to d Use "APPLICATION FC	rill or to deepen or reentry DR PERMIT—" for such pro		
SUBMIT IN TRIPLICATE				7. If Unit or CA, Agreement Designation 8. Well Name and No.
I. Type of Well Oil Gas Well Other				
2. Name of Operator Hanley Petroleum Inc.				Hanley Federal #1
3. Address and Telephone No.				
	V. Wall, Suite #1500,)1 (915) 684-8051	10. Field and Pool, or Exploratory Area
	II (Footage, Sec., T., R., M., or Survey FNL & 1932' FWL, Sec			Shugart, North, Bone Sprin 11. County or Parish, State
				Eddy, New Mexico
12. CH	ECK APPROPRIATE BOX	(s) TO INDICATE NATU	RE OF NOTICE, REPOI	RT, OR OTHER DATA
TY	PE OF SUBMISSION		TYPE OF ACTION	
	Notice of Intent	Abandonme	nt	Change of Plans
		X Recompletion	n	
Subsequent Report				Water Shut-Off
Einal Abandonment Notice			211	
	Final Abandonment Notice	Altering Ca		Conversion to Injection
	Final Abandonment Notice	Altering Ca		Dispose Water
		Other	sing	Dispose Water (Note: Report results of multiple completion on We!! Completion or Recompletion Report and Log form.)
13. Describe Propo give subsu		all pertinent details, and give pertinent d	sing ates, including estimated date of startin	Dispose Water (Note: Report results of multiple completion on Well
give subsu	sed or Completed Operations (Clearly state rface locations and measured and true ver	all pertinent details, and give pertinent d tical depths for all markers and zones p	ates, including estimated date of startin ertinent to this work.)*	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled,
13. Describe Propogive subsu 2-23-91	sed or Completed Operations (Clearly state rface locations and measured and true ver CP this A.M. 750#.	all pertinent details, and give pertinent d tical depths for all markers and zones p Bled pressure to ze	ates, including estimated date of startin ertinent to this work.)* ero in 1-1/2 hrs.	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompetion Report and Log form.) g any proposed work. If well is directionally drilled, Removed frac head &
give subsu	sed or Completed Operations (Clearly state rface locations and measured and true ver CP this A.M. 750#. installed BOP. WIH	all pertinent details, and give pertinent d tical depths for all markers and zones p Bled pressure to ze w/4-3/4" bit on 2-2	ates, including estimated date of startin ertinent to this work.)* ero in 1-1/2 hrs. 7/8" tbg. Tagged s	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompetion Report and Log form.) g any proposed work. If well is directionally drilled,
give subsu	sed or Completed Operations (Clearly state rface locations and measured and true ver CP this A.M. 750#. installed BOP. WIH unit & cleaned out Bull Plug (.60'), 2	all pertinent details, and give pertinent d tical depths for all markers and zones p Bled pressure to zet w/4-3/4" bit on 2-2 to BP @ 7923'. Circ jts 2-7/8" tbg (65.2	ates, including estimated date of startin ertinent to this work.)* ero in 1-1/2 hrs. 7/8" tbg. Tagged s c hole clean & POH. .64'), PN (4.00'),	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompetion Report and Log form.) g any proposed work. If well is directionally drilled, Removed frac head & and @ 7815'. RU reverse Ran tbg as follows: SN (1.00'), 5 jts 2-7/8"
give subsu	sed or Completed Operations (Clearly state rface locations and measured and true ver CP this A.M. 750#. installed BOP. WIH unit & cleaned out Bull Plug (.60'), 2	all pertinent details, and give pertinent d tical depths for all markers and zones p Bled pressure to ze w/4-3/4" bit on 2-2 to BP @ 7923'. Circ	ates, including estimated date of startin ertinent to this work.)* ero in 1-1/2 hrs. 7/8" tbg. Tagged s c hole clean & POH. .64'), PN (4.00'),	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompetion Report and Log form.) g any proposed work. If well is directionally drilled, Removed frac head & and @ 7815'. RU reverse Ran tbg as follows: SN (1.00'), 5 jts 2-7/8"
give subsu	sed or Completed Operations (Clearly state rface locations and measured and true ver CP this A.M. 750#. installed BOP. WIH unit & cleaned out Bull Plug (.60'), 2 tbg (165.85'), 2-7/ TP - zero. Ran pum	all pertinent details, and give pertinent d tical depths for all markers and zones p Bled pressure to zet w/4-3/4" bit on 2-7 to BP @ 7923'. Circ jts 2-7/8" tbg (65 8" x 5-1/2" TA (3.80 p & rods as follows	ates, including estimated date of startin ertinent to this work.)* ero in 1-1/2 hrs. 7/8" tbg. Tagged s c hole clean & POH. .64'), PN (4.00'), 0'), 234 jts 2-7/8" x 10' gas anch	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompetion Report and Log form.) g any proposed work. If well is directionally drilled, Removed frac head & and @ 7815'. RU reverse Ran tbg as follows: SN (1.00'), 5 jts 2-7/8" tbg (7527.75'). or, 2-1/2" x 1-1/2" x
give subsu 2-23-91 2-24-91	sed or Completed Operations (Clearly state rface locations and measured and true ver CP this A.M. 750#. installed BOP. WIH unit & cleaned out Bull Plug (.60'), 2 tbg (165.85'), 2-7/ TP - zero. Ran pum 20' Norris-O'Bannon	all pertinent details, and give pertinent d tical depths for all markers and zones p Bled pressure to zet w/4-3/4" bit on 2-3 to BP @ 7923'. Circ jts 2-7/8" tbg (65 8" x 5-1/2" TA (3.80 p & rods as follows pump w/BHD & on/off	ates, including estimated date of startin ertinent to this work.)* ero in 1-1/2 hrs. 7/8" tbg. Tagged s c hole clean & POH. .64'), PN (4.00'), 0'), 234 jts 2-7/8" . 1 x 10' gas anch f tool, [20] 7/8" x	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompetion Report and Log form.) g any proposed work. If well is directionally drilled, Removed frac head & and @ 7815'. RU reverse Ran tbg as follows: SN (1.00'), 5 jts 2-7/8" tbg (7527.75'). or, 2-1/2" x 1-1/2" x 25' rods, [190] 3/4" x
give subsu 2-23-91	sed or Completed Operations (Clearly state rface locations and measured and true ver CP this A.M. 750#. installed BOP. WIH unit & cleaned out Bull Plug (.60'), 2 tbg (165.85'), 2-7/ TP - zero. Ran pum 20' Norris-O'Bannon 25' rods, [87] 7/8"	all pertinent details, and give pertinent d tical depths for all markers and zones p Bled pressure to zet w/4-3/4" bit on 2-2 to BP @ 7923'. Circ jts 2-7/8" tbg (65 8" x 5-1/2" TA (3.80 p & rods as follows pump w/BHD & on/off x 25' rods, [1] 7/8	ates, including estimated date of startin ertinent to this work.)* ero in 1-1/2 hrs. 7/8" tbg. Tagged s c hole clean & POH. .64'), PN (4.00'), 0'), 234 jts 2-7/8" x 10' gas anch f tool, [20] 7/8" x 8" x 6 pony rod, 1	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompetion Report and Log form.) g any proposed work. If well is directionally drilled, Removed frac head & and @ 7815'. RU reverse Ran tbg as follows: SN (1.00'), 5 jts 2-7/8" tbg (7527.75'). or, 2-1/2" x 1-1/2" x 25' rods, [190] 3/4" x 'z" x 24' polished rod
give subsu 2-23-91 2-24-91	sed or Completed Operations (Clearly state rface locations and measured and true ver CP this A.M. 750#. installed BOP. WIH unit & cleaned out Bull Plug (.60'), 2 tbg (165.85'), 2-7/ TP - zero. Ran pum 20' Norris-O'Bannon 25' rods, [87] 7/8" w/1-3/4" x 14' PRL.	all pertinent details, and give pertinent d tical depths for all markers and zones p Bled pressure to zet w/4-3/4" bit on 2-2 to BP @ 7923'. Circ jts 2-7/8" tbg (65 8" x 5-1/2" TA (3.80 p & rods as follows p w/BHD & on/off x 25' rods, [1] 7/8 Hung well on & sta	ates, including estimated date of startin ertinent to this work.)* ero in 1-1/2 hrs. 7/8" tbg. Tagged s c hole clean & POH. .64'), PN (4.00'), 0'), 234 jts 2-7/8" x 10' gas anch f tool, [20] 7/8" x 8" x 6 pony rod, 1 arted operating @ 1	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, Removed frac head & and @ 7815'. RU reverse Ran tbg as follows: SN (1.00'), 5 jts 2-7/8" tbg (7527.75'). or, 2-1/2" x 1-1/2" x 25' rods, [190] 3/4" x ¹ / ₂ " x 24' polished rod 0:00 A.M. 2-23-91.
give subsu 2-23-91 2-24-91	sed or Completed Operations (Clearly state rface locations and measured and true ver CP this A.M. 750#. installed BOP. WIH unit & cleaned out Bull Plug (.60'), 2 tbg (165.85'), 2-7/ TP - zero. Ran pum 20' Norris-O'Bannon 25' rods, [87] 7/8" w/1-3/4" x 14' PRL.	all pertinent details, and give pertinent d tical depths for all markers and zones p Bled pressure to zet w/4-3/4" bit on 2-2 to BP @ 7923'. Circ jts 2-7/8" tbg (65 8" x 5-1/2" TA (3.80 p & rods as follows pump w/BHD & on/off x 25' rods, [1] 7/8 Hung well on & sta -86" SPM. CP -zero	ates, including estimated date of startin ertinent to this work.)* ero in 1-1/2 hrs. 7/8" tbg. Tagged s c hole clean & POH. .64'), PN (4.00'), 0'), 234 jts 2-7/8" x 10' gas anch f tool, [20] 7/8" x 8" x 6 pony rod, 1 arted operating @ 1 . Produced 2 BO &	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, Removed frac head & and @ 7815'. RU reverse Ran tbg as follows: SN (1.00'), 5 jts 2-7/8" tbg (7527.75'). or, 2-1/2" x 1-1/2" x 25' rods, [190] 3/4" x ¹ / ₂ " x 24' polished rod 0:00 A.M. 2-23-91.
give subsu 2-23-91 2-24-91	sed or Completed Operations (Clearly state rface locations and measured and true ver CP this A.M. 750#. installed BOP. WIH unit & cleaned out Bull Plug (.60'), 2 tbg (165.85'), 2-7/ TP - zero. Ran pum 20' Norris-O'Bannon 25' rods, [87] 7/8" w/1-3/4" x 14' PRL. Operated 20 hrs @ 8	Dother all pertinent details, and give pertinent d tical depths for all markers and zones p Bled pressure to zet w/4-3/4" bit on 2-2 to BP @ 7923'. Circ jts 2-7/8" tbg (65 8" x 5-1/2" TA (3.80 p & rods as follows pump w/BHD & on/off x 25' rods, [1] 7/8 Hung well on & sta -86" SPM. CP -zero -86" SPM. CP 30#.	ates, including estimated date of startin ertinent to this work.)* ero in 1-1/2 hrs. 7/8" tbg. Tagged s c hole clean & POH. .64'), PN (4.00'), 0'), 234 jts 2-7/8" x 10' gas anch f tool, [20] 7/8" x 8" x 6 pony rod, 1 arted operating @ 1 . Produced 2 BO &	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, Removed frac head & and @ 7815'. RU reverse Ran tbg as follows: SN (1.00'), 5 jts 2-7/8" tbg (7527.75'). or, 2-1/2" x 1-1/2" x 25' rods, [190] 3/4" x ½" x 24' polished rod 0:00 A.M. 2-23-91. 80 BW. 72 BW & 44 MCF. 1586 BLWTR.
give subsu 2-23-91 2-24-91 2-25-91 2-26-91 2-27-91	sed or Completed Operations (Clearly state rface locations and measured and true ver CP this A.M. 750#. installed BOP. WIH unit & cleaned out Bull Plug (.60'), 2 tbg (165.85'), 2-7/ TP - zero. Ran pum 20' Norris-O'Bannon 25' rods, [87] 7/8" w/1-3/4" x 14' PRL. Operated 20 hrs @ 8 Operated 24 hrs @ 8 Operated 24 hrs @ 8	all pertinent details, and give pertinent d tical depths for all markers and zones p Bled pressure to zet w/4-3/4" bit on 2-2 to BP @ 7923'. Circ jts 2-7/8" tbg (65 8" x 5-1/2" TA (3.80 p & rods as follows pump w/BHD & on/off x 25' rods, [1] 7/8 Hung well on & sta -86" SPM. CP -zero -86" SPM. CP 30#.	ates, including estimated date of startin ertinent to this work.)* ero in 1-1/2 hrs. 7/8" tbg. Tagged s c hole clean & POH. .64'), PN (4.00'), 0'), 234 jts 2-7/8" 	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompetion Report and Log form.) g any proposed work. If well is directionally drilled, Removed frac head & and @ 7815'. RU reverse Ran tbg as follows: SN (1.00'), 5 jts 2-7/8" tbg (7527.75'). or, 2-1/2" x 1-1/2" x 25' rods, [190] 3/4" x ½" x 24' polished rod 0:00 A.M. 2-23-91. 80 BW. 72 BW & 44 MCF. 1586 BLWTR. 6 BW, 93 MCF. 1500 BLWTR. BW, 113 MCF. 1445 BLWTR.
give subsu 2-23-91 2-24-91 2-25-91 2-26-91 2-27-91 2-28-91	sed or Completed Operations (Clearly state rface locations and measured and true ver CP this A.M. 750#. installed BOP. WIH unit & cleaned out Bull Plug (.60'), 2 tbg (165.85'), 2-7/ TP - zero. Ran pum 20' Norris-O'Bannon 25' rods, [87] 7/8" w/1-3/4" x 14' PRL. Operated 20 hrs @ 8 Operated 24 hrs @ 8 Operated 24 hrs @ 8 Operated 24 hrs @ 8 Operated 24 hrs @ 8	all pertinent details, and give pertinent d tical depths for all markers and zones p Bled pressure to zet w/4-3/4" bit on 2-2 to BP @ 7923'. Circ jts 2-7/8" tbg (65 8" x 5-1/2" TA (3.80 p & rods as follows pump w/BHD & on/off x 25' rods, [1] 7/8 Hung well on & sta -86" SPM. CP -zero -86" SPM. CP 30#.	ates, including estimated date of startin ertinent to this work.)* ero in 1-1/2 hrs. 7/8" tbg. Tagged s c hole clean & POH. .64'), PN (4.00'), 0'), 234 jts 2-7/8" .1" x 10' gas anch f tool, [20] 7/8" x 8" x 6" pony rod, 1 arted operating @ 1 . Produced 2 BO & Produced 32 BO & 1 Produced 114 BO, 8 Produced 86 BO, 55	 Dispose Water (Note: Report results of multiple completion on Well Completion or Recompetion Report and Log form.) g any proposed work. If well is directionally drilled, Removed frac head & and @ 7815'. RU reverse Ran tbg as follows: SN (1.00'), 5 jts 2-7/8" tbg (7527.75'). or, 2-1/2" x 1-1/2" x 25' rods, [190] 3/4" x ½" x 24' polished rod 0:00 A.M. 2-23-91. 80 BW. 72 BW & 44 MCF. 1586 BLWTR. 6 BW, 93 MCF. 1500 BLWTR. BW, 113 MCF. 1445 BLWTR.
give subsu 2-23-91 2-24-91 2-25-91 2-26-91 2-26-91 2-28-91	sed or Completed Operations (Clearly state rface locations and measured and true ver CP this A.M. 750#. installed BOP. WIH unit & cleaned out Bull Plug (.60'), 2 tbg (165.85'), 2-7/ TP - zero. Ran pum 20' Norris-O'Bannon 25' rods, [87] 7/8" w/1-3/4" x 14' PRL. Operated 20 hrs @ 8 Operated 24 hrs @ 8 Operated 24 hrs @ 8	all pertinent details, and give pertinent d tical depths for all markers and zones p Bled pressure to zet w/4-3/4" bit on 2-2 to BP @ 7923'. Circ jts 2-7/8" tbg (65 8" x 5-1/2" TA (3.80 p & rods as follows pump w/BHD & on/off x 25' rods, [1] 7/8 Hung well on & sta -86" SPM. CP -zero -86" SPM. CP 30#. -86" SPM. CP 30#. -86" SPM. CP 30#.	ates, including estimated date of startin ertinent to this work.)* ero in 1-1/2 hrs. 7/8" tbg. Tagged s c hole clean & POH. .64'), PN (4.00'), 0'), 234 jts 2-7/8" .1" x 10' gas anch f tool, [20] 7/8" x 8" x 6" pony rod, 1 arted operating @ 1 . Produced 2 BO & Produced 32 BO & 1 Produced 114 BO, 8 Produced 86 BO, 55	 Dispose Water (Note: Report results of multiple completion on Well Completion or Recompetion Report and Log form.) g any proposed work. If well is directionally drilled, Removed frac head & and @ 7815'. RU reverse Ran tbg as follows: SN (1.00'), 5 jts 2-7/8" tbg (7527.75'). or, 2-1/2" x 1-1/2" x 25' rods, [190] 3/4" x ½" x 24' polished rod 0:00 A.M. 2-23-91. 80 BW. 72 BW & 44 MCF. 1586 BLWTR. 6 BW, 93 MCF. 1500 BLWTR. BW, 113 MCF. 1445 BLWTR. BW, 105 MCF. 1423 BLWTR.
give subsu 2-23-91 2-24-91 2-25-91 2-26-91 2-26-91 2-28-91 14. Thereby certific	sed or Completed Operations (Clearly state rface locations and measured and true ver CP this A.M. 750#. installed BOP. WIH unit & cleaned out Bull Plug (.60'), 2 tbg (165.85'), 2-7/ TP - zero. Ran pum 20' Norris-O'Bannon 25' rods, [87] 7/8" w/1-3/4" x 14' PRL. Operated 20 hrs @ 8 Operated 24 hrs @ 8 Operated 2	all pertinent details, and give pertinent details, and give pertinent details and give pertinent detai	ates, including estimated date of startin ertinent to this work.)* ero in 1-1/2 hrs. 7/8" tbg. Tagged s c hole clean & POH. .64'), PN (4.00'), 0'), 234 jts 2-7/8" .1" x 10' gas anch f tool, [20] 7/8" x 8" x 6" pony rod, 1 arted operating @ 1 . Produced 2 BO & Produced 32 BO & 1 Produced 31 BO, 8 Produced 86 BO, 55 Produced 81 BO, 22	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, Removed frac head & and @ 7815'. RU reverse Ran tbg as follows: SN (1.00'), 5 jts 2-7/8" tbg (7527.75'). or, 2-1/2" x 1-1/2" x 25' rods, [190] 3/4" x ½" x 24' polished rod 0:00 A.M. 2-23-91. 80 BW. 72 BW & 44 MCF. 1586 BLWTR. 6 BW, 93 MCF. 1500 BLWTR. BW, 113 MCF. 1445 BLWTR. BW, 105 MCF. 1423 BLWTR.
give subsu 2-23-91 2-24-91 2-25-91 2-26-91 2-26-91 2-28-91 14. Thereby certific Signed (This space for Approved by	sed or Completed Operations (Clearly state rface locations and measured and true ver CP this A.M. 750#. installed BOP. WIH unit & cleaned out Bull Plug (.60'), 2 tbg (165.85'), 2-7/ TP - zero. Ran pum 20' Norris-O'Bannon 25' rods, [87] 7/8" w/1-3/4" x 14' PRL. Operated 20 hrs @ 8 Operated 24 hrs @ 8 Operated 2	all pertinent details, and give pertinent details, and give pertinent details and give pertinent detai	ates, including estimated date of startin ertinent to this work.)* ero in 1-1/2 hrs. 7/8" tbg. Tagged s c hole clean & POH. .64'), PN (4.00'), 0'), 234 jts 2-7/8" .1" x 10' gas anch f tool, [20] 7/8" x 8" x 6" pony rod, 1 arted operating @ 1 . Produced 2 BO & Produced 32 BO & 1 Produced 31 BO, 8 Produced 86 BO, 55 Produced 81 BO, 22	Dispose Water (Note: Report results of multiple completion on Well Completion or Recomparison Report and Log form.) g any proposed work. If well is directionally drilled, Removed frac head & and @ 7815'. RU reverse Ran tbg as follows: SN (1.00'), 5 jts 2-7/8" tbg (7527.75'). or, 2-1/2" x 1-1/2" x 25' rods, [190] 3/4" x ½" x 24' polished rod 0:00 A.M. 2-23-91. 80 BW. 72 BW & 44 MCF. 1586 BLWTR. 6 BW, 93 MCF. 1500 BLWTR. BW, 113 MCF. 1445 BLWTR. BW, 113 MCF. 1423 BLWTR. BW, 105 MCF. 1423 BLWTR.
give subsu 2-23-91 2-24-91 2-25-91 2-26-91 2-26-91 2-28-91 14. I hereby certific Signed (This space for Approved by	sed or Completed Operations (Clearly state rface locations and measured and true ver CP this A.M. 750#. installed BOP. WIH unit & cleaned out Bull Plug (.60'), 2 tbg (165.85'), 2-7/ TP - zero. Ran pum 20' Norris-O'Bannon 25' rods, [87] 7/8" w/1-3/4" x 14' PRL. Operated 20 hrs @ 8 Operated 24 hrs @ 8 operated 2	all pertinent details, and give pertinent details, and give pertinent details, and give pertinent details depths for all markers and zones p Bled pressure to zet w/4-3/4" bit on 2-7 to BP @ 7923'. Circo jts 2-7/8" tbg (65.4) 8" x 5-1/2" TA (3.80) p & rods as follows follows for a standard state of the set o	ates, including estimated date of startin ertinent to this work.)* ero in 1-1/2 hrs. 7/8" tbg. Tagged s c hole clean & POH. .64'), PN (4.00'), 0'), 234 jts 2-7/8" .1" x 10' gas anch f tool, [20] 7/8" x 8" x 6" pony rod, 1 arted operating @ 1 . Produced 2 BO & Produced 32 BO & 1 Produced 31 BO, 8 Produced 86 BO, 55 Produced 81 BO, 22	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, Removed frac head & and @ 7815'. RU reverse Ran tbg as follows: SN (1.00'), 5 jts 2-7/8" tbg (7527.75'). or, 2-1/2" x 1-1/2" x 25' rods, [190] 3/4" x ½" x 24' polished rod 0:00 A.M. 2-23-91. 80 BW. 72 BW & 44 MCF. 1586 BLWTR. 6 BW, 93 MCF. 1500 BLWTR. BW, 113 MCF. 1445 BLWTR. BW, 113 MCF. 1423 BLWTR. M Date 3-1-91