TEN POINT DRILLING PLAN IN COMPLIANCE WITH ORDER NO. 1

SUN EXPLORATION AND PRODUCTION COMPANY SCOGGIN DRAW FED 'B' #1 SEC. 22, T18S, R27E 1980' FSL & 660' FEL EDDY COUNTY, NEW MEXICO

1. GEOLOGIC SURFACE FORMATION: Quatenary

2. ESTIMATED TOPS OF IMPORTANT GEOLOGIC MARKERS:

Rustler	490
Queen	1010
San Andres	1800
*Glorieta	3400
*Wolfcamp	6550
*Strawn	8695
*Atoka	9020
*Morrow	9455
Chester	10030

3. ESTIMATED DEPTHS OF ANTICIPATED, WATER, OIL, GAS OR MINERALS:

Formations possibly productive of oil or gas are indicated with an asterisk (*), above in Section 2.

4. **PROPOSED CASING PROGRAM:**

Size	<u>Csg Seat</u>	Footage	Grade	<u>Wt & Thread</u>	
8-5/8" 4-1/2" 4-1/2" 4-1/2" 2-3/8"	1850'	1700' 6100' 2250' 9800'	K-55 K-55 K-55 N-80 N-80	24.0# 10.5# 10.5# 11.6# 4.7# {	STC BTC STC STC Brd EUE

PROPOSED CEMENTING PROGRAM:

8-5/8" Cemented to surface w/ 425 sx Lite + 1/4#/Sx Flocele followed by 525 sx Class "C" Neat Cemented to 8000' w/ 550 sx 50/50 Poz "H" + 2% Gel + 2% KCL + .3% CFR-2 + .5% Fluid Loss Additive

Cement volumes adjusted by calipers for 5-1/2" casing string.