

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 660' FEL of Section 22-T18S-R27E (Unit I, NESE)

10-203 FORM APPROVED
Budget Bureau No. 1004-0135
Expires. March 31, 1993

5. Lease Designation and Serial No.

LC-060122

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

NMNM87891

8. Well Name and No.

Chalk AKH Fed Com #1

9. API Well No.

30-015-26116

10. Field and Pool, or Exploratory Area

Red Lake Upper Penn, East

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Propose to plug and abandon as follows:

1. Nipple up BOP.
2. POOH with production equipment.
3. Set CIBP at 7600' and cap with 35' of cement.
4. GIH with open ended tubing. Load hole with plugging mud.
5. Spot 35 sacks Class C cement from 6782-6682' (Top of Wolfcamp at 6732').
6. Spot 35 sacks Class C cement from 3620-3520' (Top of Glorieta at 3571').
7. Spot 35 sacks Class C cement from 2050-1750' (Top of San Andres at 1996' & 8-5/8" shoe at 1800'. WOC. Tag plug.
8. Spot 15 sacks Class C cement at surface.
9. Install regulation abandonment marker.

**SEE ATTACHED FOR
CONDITIONS OF APPROVAL**

14. I hereby certify that the foregoing is true and correct

Signed [Signature]

Title Operations Technician

Date March 27, 1998

(This space for Federal or State office use)

(ORIG SGO LIES BARYAK

Title PETROLEUM ENGINEER

Date APR 08 1998

Approved by
Conditions of approval, if any: