

MARBOB ENERGY CORPORATION

Chalk "AKH" Federal SWD #1
1980' FSL and 660' FEL
Section 22-T18S-R27E
Eddy County, New Mexico

In conjunction with Form 3160-5, Sundry Notices and Reports on Wells, Marbob Energy Corporation submits the following ten items of pertinent information for the subject well in accordance with BLM requirements.

1. The geological surface formation is Alluvium:
2. The estimated tops of geologic markers are as follows:

Queen	1,127'
Grayburg	1,697'
San Andres	1,966'
Glorieta	3,751'
Bone Springs	4,438'
Abo	5,719'
Wolfcamp Lime	6,732'
Penn	7,654'
Base Penn Dolomite	8,506'
3. The estimated depths at which anticipated water, oil or gas formations are expected to be encountered:

Water:	Approximately 275'
Oil or Gas:	None
4. Proposed Casing Program: See Form 3160-5. (See attached wellbore schematics).
5. Pressure Control Equipment: See Form 3160-5 and Exhibit B.
6. Mud Program: See Form 3160-5.
7. Auxiliary Equipment: Sub with full-opening safety valve on floor.
8. Testing, Logging and Coring Program: None
9. No abnormal pressures or temperatures are anticipated.
10. Anticipated starting date: As soon as possible after approval.