

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CONTACT RECEIVING
OFFICE FOR INSTRUCTIONS ON
OF COPIES REQUIRED
(Other instructions on reverse side)

MM Roswell District
Modified Form No.
NMXO-3160-4

CISF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		34. Area Circle & Phone No. 505/677-2360		5. LEASE DESIGNATION AND SERIAL NO. LC-029395-B	
2. NAME OF OPERATOR Socorro Petroleum Company				6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P.O. Box 38, Loco Hills, NM 88255		RECEIVED		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1385' FNL & 1345' FWL		AUG -2 '90		8. FARM OR LEASE NAME Turner "B"	
14. PERMIT NO.		15. ELEVATIONS (Show whether DT, RT, GR, etc.) 3660' GR		9. WELL NO. 83	
		ARTESIA OFFICE		10. FIELD AND POOL, OR WILDCAT Grayburg-Jackson	
				11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 29-17S-31E	
				12. COUNTY OR PARISH Eddy	
				13. STATE NM	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANE ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐
REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROMISED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

7/20/90 Drilled to 3495' T.D. Ran DLL, MLL, GR & ZOLC, CN, GR.
Ran 79 jts. 5 1/2" 17# J-55 casing. Set @ 3493'. Cemented w/425 sx. Howco lite w/6# salt, 3/10% CFR-2, followed by 525 sx. Cl. C w/5# salt 4/10% CFR-2. Plug down @ 2:30 a.m. Circ. 70 sx. to pit.

RECEIVED
JUL 30 8 41 AM '90
CARLSBAD AREA OFFICE

ACCEPTED FOR RECORD

AL

JUL 30 1990

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED John J. Smith TITLE Agent

DATE 7/27/90

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

*See Instructions on Reverse Side