

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CONTACT RECEIVED
OFFICE FOR NAL
OF COPIES REQUIRED
(Other instructions on re-
verse side)

MM Rowell District
Modified Form No.
11160-3160-4

45F

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Socorro Petroleum Company ✓		8. FARM OR LEASE NAME Turner "B"	
3. ADDRESS OF OPERATOR P.O. Box 38, Loco Hills, NM 88255		9. WELL NO. 84	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1305' FNL & 2525' FEL		10. FIELD AND POOL, OR WILDCAT Grayburg Jackson	
11. SURV. T., S., M., OR B.L. AND SURVY OR ARDA		12. COUNTY OR PARISH Eddy	
13. STATE NM		14. PERMIT NO.	
15. ELEVATIONS (Show whether DF, RT, or, etc.) 3726' GR 3737' KB		16. NOV 9 '90	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	☐	PULL OR ALTER Casing	☐
FRACTURE TREAT	☐	MULTIPLE COMPLETION	☐
SHUT IN OR ACIDIZ	☐	ABANDON*	☐
REPAIR WELL	☐	CHANGE PLANS	☐
(Other) ☐			

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	☐	REPAIRING WELL	☐
FRACTURE TREATMENT	☒	ALTERING CASING	☐
SHUTTING OR ACIDIZING	☒	ABANDONMENT*	☐
(Other) ☐			

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and none pertinent to this work.)

10-15-90 Ran cement bond log. Perf. 3467'-72' with 1 hole/Ft.
10-16-90 Acidized perfs w/1000 gal. 15% NeFe acid. Swabbed well back.
10-17-90 Perf. 3365'-67' 3 holes
3342'-47' 6 holes
3328'-33' 6 holes
3300'-02' 3 holes
Acidized perfs. w/2500 gal. 15% NeFe. Swabbed well back.
Perf. 3228'-32' 5 holes
3157'-59' 3 holes
3120'-22' 3 holes
10-18-90 Acidized perfs. w/1500 gal. 15% NeFe. Swabbed well back.
10-19-90 Frac'd well w/80,000 gal. 30# cross link gel, 130,000# 20/40 sand and 40,000# 12/20 sand. Max. press. 3200#, min. press. 2850#, ISIP 2660#, ARI 30 BPM.

RECEIVED
NOV 2 11 43 AM '90
CARTER AREA

18. I hereby certify that the foregoing is true and correct

SIGNED Walter J. Lyle TITLE Consultant DATE 11/1/90

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side