Form 3160-5 (November 1983) (Formerly 9-331) DEPARTMENT THE INTERIOR BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON V			Budget Bureau No. 1004-0135 CS Expires August 31, 1985 5. LEASE DESIGNATION AND SERIAL NO. LC-054205 6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
(Do not use this form for propos Use "APPLICA	CES AND REPORTS O als to drill or to deepen or plug bau TION FOR PERMIT—" for such pro			
OIL GAB GAB OTHER		AUG 17 '90	7. UNIT AGREEMENT NA	ME
NAME OF OPERATOR		13 C	8. FARM OR LEASE NAM	(E
Hondo Oil & Gas Company 3. Address of Operator		AND SHAL OF L	Pitcher Federal 9. WBLL NO.	
P. O. Box 2208, Roswell	L, NM 88202		1	
LOCATION OF WELL (Report location cl See also space 17 below.)		tate requirements.*	10. FIELD AND POOL, OF	N WILDCAT
At surface			West Red Lak	
/700 990' FNL & 1650' FWL			11. SEC., T., E., M., OR B SURVEY OB ARKA	LK. AND
JOG FRE & 4050 FRE			Sec.8-T185-R2	7E
. PERMIT NO.	15. ELEVATIONS (Show whether DF, F	IT, GR, etc.)	12. COUNTY OR PARISH	
· · · · · · · · · · · · · · · · · · ·	3373' GR		Eddy	NM
Check Ap	propriate Box To Indicate Na	ture of Notice, Report, or C	Other Data	
NOTICE OF INTEN	TION TO :	SUBSEQ	DENT REPORT OF :	
TEST WATER SHUT-OFF	CLL OR ALTER CASING	WATER SHUT-OFF	BEPAIRING W	
PRACTURE TREAT	ULTIPLE COMPLETE	FRACTUBE TREATMENT	ALTERING CA	SING
	BANDON*	SHOOTING OR ACIDIZING	ABANDONMEN	T •
	HANGE PLANS	(Other)	of multiple completion of	Well
			ation Banant and Tour	
			including estimated date al depths for all markers	m.) e of starting any and gones perti-
DESCRIBE PROPOSED OR COMPLETED OPEF proposed work. If well is direction nent to this work.)* Spudded well 8 5/8" 24# C + 150 sx. C	L 8/5/90. Drilled 12 J-55 casing and set @ Lass "C" cement. Circ A BOP to 500# for 15 m	details, and give pertiment dates, ns and measured and true vertice 1/4" hole to 1109'. 1095'. Cemented wit ulated cement to sur	ncluding estimated date al depths for all markers Ran 25 jts. Th 400 sx. Lite fface. WOC 9	m.) e of starting any and zones perti-
DESCRIBE PROPOSED OR COMPLETED OPEF proposed work. If well is direction nent to this work.)* Spudded well 8 5/8" 24# C + 150 sx. Cl hrs. Tested	L 8/5/90. Drilled 12 J-55 casing and set @ Lass "C" cement. Circ A BOP to 500# for 15 m	details, and give pertiment dates, ns and measured and true vertice 1/4" hole to 1109'. 1095'. Cemented wit ulated cement to sur	ncluding estimated date al depths for all markers Ran 25 jts. Th 400 sx. Lite fface. WOC 9	m.) e of starting any and zones perti-
DESCRIBE PROPOSED OR COMPLETED OPER proposed work. If well is direction nent to this work.)* Spudded well 8 5/8" 24# C + 150 sx. Cl hrs. Tested	L 8/5/90. Drilled 12 J-55 casing and set @ Lass "C" cement. Circ A BOP to 500# for 15 m	details, and give pertiment dates, ns and measured and true vertice 1/4" hole to 1109'. 1095'. Cemented wit ulated cement to sur	ncluding estimated date al depths for all markers Ran 25 jts. Th 400 sx. Lite fface. WOC 9	of starting any and zones perti-
DESCRIBE PROPOSED OR COMPLETED OPER proposed work. If well is direction nent to this work.)* Spudded well 8 5/8" 24# C + 150 sx. Cl hrs. Tested	L 8/5/90. Drilled 12 J-55 casing and set @ Lass "C" cement. Circ A BOP to 500# for 15 m	details, and give pertiment dates, ns and measured and true vertice 1/4" hole to 1109'. 1095'. Cemented wit ulated cement to sur	ncluding estimated date al depths for all markers Ran 25 jts. Th 400 sx. Lite fface. WOC 9	of starting any and zones perti-
DESCRIBE PROPOSED OR COMPLETED OPER proposed work. If well is direction nent to this work.)* Spudded well 8 5/8" 24# C + 150 sx. Cl hrs. Tested	L 8/5/90. Drilled 12 J-55 casing and set @ Lass "C" cement. Circ A BOP to 500# for 15 m	details, and give pertiment dates, ns and measured and true vertice 1/4" hole to 1109'. 1095'. Cemented wit ulated cement to sur	ncluding estimated date al depths for all markers Ran 25 jts. Th 400 sx. Lite fface. WOC 9	of starting any and zones perti-
DESCRIBE PROPOSED OR COMPLETED OPER proposed work. If well is direction nent to this work.)* Spudded well 8 5/8" 24# C + 150 sx. Cl hrs. Tested	L 8/5/90. Drilled 12 J-55 casing and set @ Lass "C" cement. Circ A BOP to 500# for 15 m	details, and give pertiment dates, ns and measured and true vertice 1/4" hole to 1109'. 1095'. Cemented wit ulated cement to sur	ncluding estimated date al depths for all markers Ran 25 jts. Th 400 sx. Lite fface. WOC 9	of starting any and zones perti-
DESCRIBE PROPOSED OR COMPLETED OPEF proposed work. If well is direction nent to this work.)* Spudded well 8 5/8" 24# C + 150 sx. Cl hrs. Tested	L 8/5/90. Drilled 12 J-55 casing and set @ Lass "C" cement. Circ A BOP to 500# for 15 m	details, and give pertiment dates, ns and measured and true vertice 1/4" hole to 1109'. 1095'. Cemented wit ulated cement to sur	ncluding estimated date al depths for all markers Ran 25 jts. Th 400 sx. Lite fface. WOC 9	of starting any and zones perti-
<pre>proposed work. If well is direction nent to this work.)* Spudded well 8 5/8" 24# 0 + 150 sx. Cl hrs. Tested</pre>	L 8/5/90. Drilled 12 J-55 casing and set @ Lass "C" cement. Circ A BOP to 500# for 15 m	details, and give pertiment dates, ns and measured and true vertice 1/4" hole to 1109'. 1095'. Cemented wit ulated cement to sur	Ran 25 jts. ch 400 sx. Lite face. WOC 9 cilled out with	of starting any and zones perti-
DESCRIBE PROPOSED OR COMPLETED OPEF proposed work. If well is direction nent to this work.)* Spudded well 8 5/8" 24# C + 150 sx. Cl hrs. Tested	L 8/5/90. Drilled 12 J-55 casing and set @ Lass "C" cement. Circ A BOP to 500# for 15 m	details, and give pertiment dates, ns and measured and true vertice 1/4" hole to 1109'. 1095'. Cemented wit ulated cement to sur	ncluding estimated date al depths for all markers Ran 25 jts. Th 400 sx. Lite fface. WOC 9	of starting any and zones perti-
<pre>proposed work. If well is direction nent to this work.)* Spudded well 8 5/8" 24# 0 + 150 sx. Cl hrs. Tested</pre>	L 8/5/90. Drilled 12 J-55 casing and set @ Lass "C" cement. Circ A BOP to 500# for 15 m	details, and give pertiment dates, ns and measured and true vertice 1/4" hole to 1109'. 1095'. Cemented wit ulated cement to sur	Ran 25 jts. ch 400 sx. Lite face. WOC 9 cilled out with	of starting any and zones perti-
<pre>proposed work. If well is direction nent to this work.)* Spudded well 8 5/8" 24# 0 + 150 sx. Cl hrs. Tested</pre>	L 8/5/90. Drilled 12 J-55 casing and set @ Lass "C" cement. Circ A BOP to 500# for 15 m	details, and give pertiment dates, ns and measured and true vertice 1/4" hole to 1109'. 1095'. Cemented wit ulated cement to sur	Ran 25 jts. ch 400 sx. Lite face. WOC 9 cilled out with	of starting any and zones perti-
DESCRIBE PROPOSED OR COMPLETED OPER proposed work. If well is direction nent to this work.)* Spudded well 8 5/8" 24# C + 150 sx. Cl hrs. Tested	L 8/5/90. Drilled 12 J-55 casing and set @ Lass "C" cement. Circ A BOP to 500# for 15 m	details, and give pertiment dates, ns and measured and true vertice 1/4" hole to 1109'. 1095'. Cemented wit ulated cement to sur	Ran 25 jts. ch 400 sx. Lite face. WOC 9 cilled out with	of starting any and zones perti-
DESCRIBE PROPOSED OR COMPLETED OPER proposed work. If well is direction nent to this work.)* Spudded well 8 5/8" 24# J + 150 sx. CJ hrs. Tested 7 7/8" bit 8	1 8/5/90. Drilled 12 J-55 casing and set @ Lass "C" cement. Circ 1 BOP to 500# for 15 m 3/9/90.	details, and give pertiment dates, ns and measured and true vertice 1/4" hole to 1109'. 1095'. Cemented wit ulated cement to sur	Ran 25 jts. ch 400 sx. Lite face. WOC 9 cilled out with	of starting any and zones perti-
DESCRIBE PROPOSED OR COMPLETED OPER proposed work. If well is direction nent to this work.)* Spudded well 8 5/8" 24# J + 150 sx. CJ hrs. Tested 7 7/8" bit 8	1 8/5/90. Drilled 12 J-55 casing and set @ Lass "C" cement. Circ 1 BOP to 500# for 15 m 3/9/90.	details, and give pertiment dates, ns and measured and true vertice 1/4" hole to 1109'. 1095'. Cemented wit ulated cement to sur	Ran 25 jts. ch 400 sx. Lite face. WOC 9 cilled out with	of starting any and zones perti-
DESCRIBE PROPOSED OR COMPLETED OPER proposed work. If well is direction nent to this work.)* Spudded well 8 5/8" 24# J + 150 sx. CJ hrs. Tested 7 7/8" bit 8	true and correct	details, and give pertiment dates, ns and measured and true vertice 1/4" hole to 1109'. 1095'. Cemented wit ulated cement to sur	Ran 25 jts. ch 400 sx. Lite face. WOC 9 cilled out with	of starting any and zones perti-
DESCRIBE PROPOSED OR COMPLETED OPEF proposed work. If well is direction nent to this work.)* Spudded well 8 5/8" 24# C + 150 sx. Cl hrs. Tested	1 8/5/90. Drilled 12 J-55 casing and set @ Lass "C" cement. Circ 1 BOP to 500# for 15 m 3/9/90. true and correct TITLE Engi	detalls, and give pertinent dates, ns and measured and irue vertice 1/4" hole to 1109'. 1095'. Cemented wit culated cement to sur in held okay. Dr	Including estimated date al depths for all markers Ran 25 jts. th 400 sx. Lite cface. WOC 9 cilled out with	of starting any and zones perti-
 DESCRIBE PROPOSED OR COMPLETED OPER proposed work. If well is direction nent to this work.)* Spudded well 8 5/8" 24# c + 150 sx. C] hrs. Tested 7 7/8" bit 8 7 7/8" bit 8 I hereby certify that the foregoing is SIGNED 15 20 15 20 15 20 10 10 10 10 10 10 10 10 10 10 10 10 10	1 8/5/90. Drilled 12 J-55 casing and set @ Lass "C" cement. Circ 1 BOP to 500# for 15 m 3/9/90. true and correct TITLE Engi	detalls, and give pertinent dates, ns and measured and irue vertice 1/4" hole to 1109'. 1095'. Cemented wit culated cement to sur in held okay. Dr	Including estimated date al depths for all markers Ran 25 jts. th 400 sx. Lite cface. WOC 9 cilled out with	of starting any and zones perti-

*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

.