Form 3160-5 (June 1990)

Approved by

Conditions of approval, if any:

TED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

OIL COME COMMISSION Drawer OD Artesia, NM 88210

FORM APPROVED

Budget Bureau No 1004-0135 Expires March 31 1993 5. Lease Designation and Serial No. SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. NMNM7713 Use "APPLICATION FOR PERMIT—" for such proposals of 6. If Indian, Allottee or Tribe Name SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation 1. Type of Well ☐ Gas Well ⊠ Oil Well Other West Red Lake Unit 8910069700 8. Well Name and No. 0/07 2. Name of Operator **DEVON ENERGY CORPORATION (NEVADA)** West Red Lake Unit #50 9. API Well No. 3. Address and Telephone No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 78,108 (405)552-4511 30-015-26428 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Red Lake (Q-GB-SA) Sec C-8-T18S-R27E 990' FNL & 1700' FWL 11. County or Parish, State Eddy County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Notice of Intent Abandonment Change of Plans Recompletion New Construction Plugging Back Subsequent Report Non Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing NOVO E 1945 Conversion to Injection Other Stimulation of San Andres (revised) Dispose Water (Note: Report results of multiple completion on Well or Recompletion Report and Log form.) 13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including ed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* DIST. 2 10/13/94 thru 10/14/95 POH w/pump, rods and tbg. Wedge ran CIBP, and set at 2200' and capped w/ 2 sx cement. 10/14/94 RU Wedge. Perforated the San Andres "C" & "D" through 4 1/2" casing using 3 1/8" select fire gun at 1876', 74', 70', 66', 62', 58', 54', 50', 46', 42', 38', 34', 18', 14', 10', 1928', 26', 08', 06', 04', 02'; 21 holes (.40"EHD). 10/15/94 Set packer at 1700'. Nowsco acidized perfs 1810-1928' w/ 2500 gals 15% NeFe + 40 BS. POH w/packer. 10/16/94 RIH w/RBP, set at 1800'. RU Wedge. Perforated the San Andres "A" & "B" through 4 1/2" casing using 3 1/8" select fire gun from 1710' to 1788' and 1644' to 1690'; 20 holes (.40" EHD). Ran packer, set at 1550'. 10/17/94 Nowsco acidized perfs 1644-1788' w/ 2500 gals 15% NeFe + 40 BS. POH w/ packer and RBP. Frac'd perfs 1644-1928' w/ 29,652 gals X-Link gel + 30,000# 16/30 sand + 23,860# 16/30 RC sand. 10-18-94 Cleaned out sand. Ran tbg, pump and rods. Set SN at 1970'. Pump testing. 14. I hereby certify that the foregoing is true and correct Candace R. Graham Engineering Tech. Title Date 9/21/95 (This space for Federal or State office use)

> *5*3S 001 **26 199**5

Title