State of New Mexico RECEIVED, Minerals and Natural Resources Department PR 1 5 1991 Submit 3 Copies Form C-103 to Appropriate Revised 1-1-89 District Office **DISTRICT I** OIL CONSERVATION DIVISION P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 RECEIVED ART 19 19 Alsama Fe, New Mexico 87504-2088 -015-26654 P.O. Drawer DD, Artesia, NVR 88210 5. Indicate Type of Lease MAR & 5 1991 CCE STATE FEE | DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. O. C. U. B-7071-15 SUNDRY NOTICES AND REPORTS ON WELLS ( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR RECEIVED TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) APR 2 9 199 LOCO HILLS STATE 1. Type of Well: WELL X WELL. OTHER O. C. D. ARTESIA, OFFICE 2. Name of Operator 8. Well No. Mewbourne Oil Company, 2 Address of Operator 9. Pool name or Wildcat P. O. Box 7698, Tyler, Texas 75711 Undesignated Bone Springs 4. Well Location 1980 Feet From The South West Feet From The Line Eddy Range Township Section **NMPM** County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3518' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK **ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS** COMMENCE DRILLING OPNS. **PLUG AND ABANDONMENT PULL OR ALTER CASING** CASING TEST AND CEMENT JOB | X OTHER: OTHER:\_ 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 3/14/91 - Spud at 9:30 AM 3/13/91. Ran 15 jts 13-3/8" casing set at 526' cemented with 100 sxs Thixset w/15# Gilsonite, 2# Flocele, 3% CaCl, + 250 sxs HLC w/5# Gilsonite, ¼# Flocele, 3% CaCl + 150 sxs Class "C" w/3% CaCl. Plug down at 11:30 PM. Circulated 10 sxs cement. Pressure tested to 1000# for 30 mins. Held OK. WOC 12 hrs. 3/22/91 - Ran 83 jts 8-5/8" 32# K-55 ST&C Casing set at 3630' cemented with 1400 sxs HLC w/4# Flocele, 5# Gilsonite, 12# salt followed by 300 sxs Prem Plus w/2% CaCl. Plug down at 9:15 PM. Circulated 50 sxs.

I hereby certify that the information above is present complete to the total of my knowledge and belief.

SIGNATURE TYPE OR PRINT NAME THE Engr. Oprns. Secretary DATE 3/22/91

TYPE OR PRINT NAME ORIGINAL SIGNED BY

Pressure tested casing to 1000# for 30 mins - held okay.

MIKE WILLIAMS

APPROVED BY SUPERVISOR, DISTRICT I

APR 3 0 1991

· 1.50 以 建物

to police police or profes

> Marketit englisher Oran den ene Sette til englisher