

+ csl  
dp

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

RECEIVED  
APR - 9 1992

O. C. D.  
ARTESIA OFFICE

WELL API NO. 30-015-26967
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-9891

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	7. Lease Name or Unit Agreement Name West Dayton AJR State Com
2. Name of Operator YATES PETROLEUM CORPORATION	8. Well No. 1
3. Address of Operator 105 South 4th St., Artesia, NM 88210	9. Pool name or Wildcat Und. West Atoka Morrow
4. Well Location Unit Letter <u>N</u> : <u>990</u> Feet From The <u>South</u> Line and <u>2310</u> Feet From The <u>West</u> Line Section <u>16</u> Township <u>18S</u> Range <u>26E</u> NMPM <u>Eddy</u> County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3366' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
<b>NOTICE OF INTENTION TO:</b>	<b>SUBSEQUENT REPORT OF:</b>
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.  
Spudded 26" hole 5:00 PM 3-26-92. Set 80' of 20" conductor pipe. Redi-Mix to surface. Notified NMOCD, Artesia, NM of spud. Resumed drilling 17½" hole 6:30 AM 4-2-92. Ran 12 joints 13-3/8" 48# J-55 casing set 518'. Guide shoe set 518', insert float set 474'. Cemented w/450 sx PSL + 10#/sx Gilsonite + 1/2#/sx Celloseal + 2% CaCl2 (yield 1.98, wt 12.6). Tail in w/100 sx Class "C" + 2% CaCl2 (yield 1.32, wt 14.6). PD 2:00 PM 4-2-92. Bumped plug to 200#, released pressure and float did not hold. Circulated 110 sx to surface. WOC. Drilled out 9:00 AM 4-3-92. WOC 19 hrs. NU and tested to 500# for 30 minutes, OK. Reduced hole to 12½" and resumed drilling. Note: Witnessed by Mike Stubblefield, NMOCD, Artesia, NM. 4-4-92. Ran 30 joints 8-5/8" 24# casing set 1310'. Guide shoe set 1310', float collar set 1266'. Cemented w/200 sx "H" + 12% Thicksolite + 10#/sx Gilsonite + 1/2#/sx Celloseal + 2% CaCl2 (yield 1.75, wt 14.0). Tail in w/200 sx "C" Neat + 2% CaCl2 (yield 1.32, wt 14.8). PD 8:15 AM 4-4-92. Bumped plug to 750 psi, float held OK. Cement did not circulate. WOC 4 hrs. Ran Temp. Survey and found TOC 700'. Ran 2 stages of 1", cemented w/500 sx "C". Circulated 10 sx to surface. PD 4:15 PM 4-4-92. WOC. Drilled out 5:45 AM 4-5-92. WOC 21 hrs, 30 mins. NU and tested to 1000# for 30 mins. Witnessed by Mike Stubblefield, NMOCD, Artesia, NM.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.  
SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 4-6-92  
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY  
MIKE WILLIAMS  
SUPERVISOR, DISTRICT II

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE APR 15 1992

CONDITIONS OF APPROVAL, IF ANY: