

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

dsf
Op

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

AUG 03 1992

O.C.D.

WELL API NO.
30-015-26967

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
E-9891

7. Lease Name or Unit Agreement Name

West Dayton AJR State Com

8. Well No.
1

9. Pool name or Wildcat
Undes. Strawn

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER RECOMPLETION

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter N : 990 Feet From The South Line and 2310 Feet From The West Line
Section 16 Township 18S Range 26E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3366' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK ☐ ALTERING CASING ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐ CASING TEST AND CEMENT JOB ☐
OTHER: ☐ OTHER: Plugback, perforate, treat ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-17-92. RUPU. Set CIBP 8875' w/35' cement cap. Tested casing to 2600 psi. Perforated 10 - .42" holes (2 SPF) as follows: 8724, 25, 26, 27 and 8728'. Acidized perfs 8724-28' w/1500g. 15% NEFE acid. Swabbed well - no water - no gas. Set CIBP at 8700' w/35' cement cap. Perforated 8220-8332' w/28 - .42" holes (2 SPF) as follows: 8220, 21, 22, 23, 27, 28, 29 (14), 8317, 18, 19, 29, 30, 31 and 8332' (14). Acidized perfs 8317-32' w/2500g. 15% NEFE Acidized perfs 8220-29' w/30000 SCF N2 pad, 2000g. 7 1/2% Morlfo acid with 1000 SCR N2/bbl. Frac'd perfs 8220-29' w/12375g. X-link gel + CO2 and 12000# 20/40 sand.
7-25-92 - 7-30-92. Flowed/swabbed/tested well.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 7-31-92
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY [Signature] TITLE SUPERVISOR, DISTRICT II DATE AUG 10 1992
CONDITIONS OF APPROVAL, IF ANY: