

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87508

WELL API NO.  
30-015-27009

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
E-1286

7. Lease Name or Unit Agreement Name

Turkey Track "15" State

8. Well No.

1

9. Pool name or Wildcat

Illinois Camp North Morrow

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator  
Mewbourne Oil Company

3. Address of Operator  
P.O. Box 5270 Hobbs, New Mexico 88241

4. Well Location  
Unit Letter E : 1980 Feet From The North Line and 990 Feet From The West Line  
Section 15 Township 18S Range 28E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3597' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-30-92 Drilled 26" hole to a depth of 40'. Ran 46' of 20" conductor casing. Cemented with 6 cubic yards of redi-mix.  
12-31-92 WOC. Shut down for holiday.  
01-01-93 Drilled 17-1/2" hole to a depth of 390' KB. Ran 9 jts. of 13-3/8" 48# H-40 new ST&C casing and set @ 390' KB. Cemented with 375 sx. Class "C" Lite containing 2% CaCl<sub>2</sub> + 1/4# PPS floccle slurry volume 701 cu. ft. Tailed in w/150 sx. of Class "C" Neat containing 2% CaCl<sub>2</sub>. Slurry volume is 201 cu. ft. Total slurry volume is 902 cu. ft. Comp. strength for tail slurry is 1350 psi in 12 hrs. @ 70°F. Est. form. temp. is 68°F, est. slurry temp. was 71°F. Plug down to 350' @ 7:15 a.m. 01/02/93. Circulated 47 sks. to pit. WOC 15 1/4 Hrs. NU BOP & pressure tested blind & pipe rams to 600# for 30 min. each. Held ok.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Kelly Ryan TITLE District Supt.

DATE 01/11/93  
(505)

TYPE OR PRINT NAME Kelly Ryan

TELEPHONE NO. 393-5905

(This space for State Use) ORIGINAL SIGNED BY

MIKE WILLIAMS

APPROVED BY SUPERVISOR, DISTRICT II

TITLE

DATE

JAN 25 1993

CONDITIONS OF APPROVAL, IF ANY: