

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies
DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

Form C-105
Revised 1-1-89

CISE
Blum
Baker
Sed

WELL API NO.

30-015-27009

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

E-1286

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:

OIL WELL ☐

GAS WELL ☒

DRY ☐

OTHER ☐

b. Type of Completion:

NEW
WELL ☒

WORK
OVER ☐

DEEPEN ☐

PLUG
BACK ☐

DIFF
RESVR ☐

OTHER ☐

7. Lease Name or Unit Agreement Name

Turkey Track "15" State

2. Name of Operator

Mewbourne Oil Company

3. Address of Operator

P.O. Box 5270 Hobbs, New Mexico 88241

8. Well No.

1

9. Pool name or Wildcat

Illinois Camp Morrow, North

4. Well Location

Unit Letter E : 1980 Feet From The North Line and 990 Feet From The West Line

Section 15

Township 18S

Range 28E

NMPM

Eddy

County

10. Date Spudded

12/30/92

11. Date T.D. Reached

02/09/93

12. Date Compl. (Ready to Prod.)

02/19/93

13. Elevations (DF & RKB, RT, GR, etc.)

3597' GR 3609' KB

14. Elev. Casinghead

3597'

15. Total Depth

10,870'

16. Plug Back T.D.

10,816'

17. If Multiple Compl. How

Many Zones? ---

18. Intervals

Drilled By

X

Cable Tools

19. Producing Interval(s), of this completion - Top, Bottom, Name

10,697'-10,714' Lower Morrow

20. Was Directional Survey Made

Yes

21. Type Electric and Other Logs Run

SDL-DSN, DLL-MSFL-GR, Sonic, CBL

22. Was Well Cored

No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB/FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
13-3/8"	48#/ft.	390'	17-1/2"	525 sx. Class "C"	Circulated
9-5/8"	36#/ft.	2623'	12-1/4"	1000 sx. Class "C" 800	sx. Circulated
5-1/2"	17#/ft.	10864'	8-3/4"	2470 sx. Class "H"	Circulated

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2-7/8"	10,619'	10,605'

25. TUBING RECORD

26. Perforation record (interval, size, and number)

10,697'-10,714', 17', 4 spf 62 holes

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
10,697'-10,714'	2500 gal 7 1/2% HCl w/1000
	SCF/BBL Nitrogen

28. PRODUCTION

Date First Production		Production Method (Flowing, gas lift, pumping - Size and type pump)					Well Status (Prod. or Shut-in)	
02/19/93		Flowing					Producing	
Date of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl.	Gas - MCF	Water - Bbl.	Gas - Oil Ratio	
02/21/93	12	3/4"		0	50	0	----	
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)		
5#	Packer		0	100	0	----		

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Flared

Test Witnessed By

Erick W. Nelson

30. List Attachments

Logs

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature

Erick W. Nelson

Printed Name

Erick W. Nelson

Title Engineer

Date 4/05/93

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____
 T. Salt _____ 473'
 B. Salt _____ 585'
 T. Yates _____ 749'
 T. 7 Rivers _____
 T. Queen _____ 1702'
 T. Grayburg _____
 T. San Andres _____ 2494'
 T. Glorieta _____
 T. Paddock _____
 T. Blinbry _____
 T. Tubb _____
 T. Drinkard _____
 T. Abo _____
 T. Wolfcamp _____ 7897'
 T. Penn _____ 8764'
 T. Cisco (Bough C) _____

T. Canyon _____
 T. Strawn _____ 9392'
 T. Atoka _____ 10,046'
 T. Miss _____ 10,720'
 T. Devonian _____
 T. Silurian _____
 T. Montoya _____
 T. Simpson _____
 T. McKee _____
 T. Ellenburger _____
 T. Gr. Wash _____
 T. Delaware Sand _____
 T. Bone Springs _____ 3655'
 T. Morrow Lime _____ 10,170'
 T. Morrow Clastics _____ 10,260'
 T. _____
 T. _____

Northwestern New Mexico

T. Ojo Alamo _____
 T. Kirtland-Fruitland _____
 T. Pictured Cliffs _____
 T. Cliff House _____
 T. Menefee _____
 T. Point Lookout _____
 T. Mancos _____
 T. Gallup _____
 Base Greenhorn _____
 T. Dakota _____
 T. Morrison _____
 T. Todilto _____
 T. Entrada _____
 T. Wingate _____
 T. Chinle _____
 T. Permian _____
 T. Penn "A" _____

T. Penn. "B" _____
 T. Penn. "C" _____
 T. Penn. "D" _____
 T. Leadville _____
 T. Madison _____
 T. Elbert _____
 T. McCracken _____
 T. Ignacio Otzte _____
 T. Granite _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ 10,697' to _____ 10,714' _____
 No. 2, from _____ to _____ _____
 No. 3, from _____ to _____ _____
 No. 4, from _____ to _____ _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ None _____ to _____ feet _____
 No. 2, from _____ to _____ feet _____
 No. 3, from _____ to _____ feet _____

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0'	473'	473'	Redbed and Anhydrite				
473'	585'	112'	Salt				
585'	2100'	1515'	Shale and Dolomite and Anhydrite				
2100'	3700'	1600'	Shale and Dolomite				
3700'	6400'	2700'	Limestone and Shale				
6400'	6800'	400'	Sandstone and Dolomite				
6800'	7500'	700'	Limestone and Shale				
7500'	8100'	600'	Limestone, Dolomite and Sandstone				
8100'	10250'	2150'	Limestone and Shale				
10250'	10720'	470'	Sandstone and Shale				
10720'	10870'	150'	Shale				