

155

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

# OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87500

JUL -19 1992

WELL API NO.  
30-015-27028

5. Indicate Type of Lease  
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator  
YATES PETROLEUM CORPORATION

3. Address of Operator  
105 South 4th St., Artesia, NM 88210

4. Well Location  
Unit Letter L : 2162 Feet From The South Line and 660 Feet From The West Line

Section 17 Township 18S Range 216 NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3404' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: Set Intermediate Casing ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 29 jts 9-5/8" 36# J-55 casing set 1300'. Guide shoe set 1300', insert float set 1255'. Cmt'd w/200 sx Class "C" Premium Thickset w/12% Calseal + 10# Gilsonite + 1/2# Flosceal w/2% CaCl2 (yield 1.41, wt 14.6), and 900 sx Class "C" Lite w/10# Gilsonite, 1/2# Floseal + 3% CaCl2 (yield 1.84, wt 12.7). Tail in w/200 sx Class "C" Neat w/2% CaCl2 (yield 1.33, wt 14.5). PD 3:30 PM 7-9-92. Bumped plug to 600 psi, float held okay. Cement did not circulate. WOC 4 hrs. Ran Temperature Survey and found TOC at 740'. Ran 1". Tag cement 740'. Spotted 75 sx Class "C" Neat w/3% CaCl2. PD 9:30 PM 7-10-92. WOC 4 hrs. Ran 1". Tagged cement 540'. Spotted 195 sx Class "C" Neat w/3% CaCl2. PD 2 30 AM 7-10-92. Circulated 20 sacks cement to pit on second stage of 1". WOC. Drilled out 9:30 AM 7-10-92. WOC 18 hrs. NU and tested to 1000 psi for 15 minutes, held OK. Reduced hole to 7-7/8" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 7-13-92  
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY  
MIKE WILLIAMS

APPROVED BY SUPERVISOR, DISTRICT II TITLE SUPERVISOR DATE JUL 21 1992

CONDITIONS OF APPROVAL, IF ANY: