

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit B, 660' FNL & 1330' FEL, Sec. 27-T18S-R27E

5. Lease Designation and Serial No.
LC 060122

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Chalk AKH Federal #2

9. API Well No.

30-015-27034

10. Field and Pool, or Exploratory Area

Undesignated Morrow

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Set production casing
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 10225'. Reached TD 1-18-92. Ran 250 joints 5-1/2" 17#, 23# and 26#, N-80 and J-55 LT&C casing set at 10225'. Float shoe set 10225', float collar set 10184'. Cemented in two stages as follows: Stage I - 500 gals WMW-1, 500 gals Surebond + 850 sx "H" with 8#/sx CSE + .35% Thrifty Lite + 6% CF-14 + 1/4#/sx Celloseal + 5#/sx Gilsonite (yield 1.76, wt 13.6). PD 12:00 PM 1-21-93. Pumped 1 bbl over calculated displacement. Did not bump plug. WOC 24 hours.

RECEIVED
JAN 26 10 43 AM '93
C/O
ARD

14. I hereby certify that the foregoing is true and correct

Signed

ACCEPTED FOR RECORD

Title Production Supervisor

Date 1-25-93

(This space for Federal or State office use)

Approved by (ORIG. SGD.) DAVID R. GLASS
Condition of approval, if any: 4 1993

Title

Date